


# COMPENDIUM ON HARVEST& POST HARVEST MACHINE ASSISTANT TECHNICIAN

QP ID - AGR/Q1116 NSQF LEVEL - 2





ICAR- Agricultural Technology Application Research Institute, Kolkata, Zone -V





Directorate of Extension Education Odisha University of Agriculture and Technology Bhubaneswar





Prof. Prasannajit Mishra Dean, Extension Education, OUAT

#### **MESSAGE**

It is a pleasure to learn that, Krishi Vigyan Kendra, OUAT, Nayagarh is conducting a skill Development Training program on "Harvest and Post Harvest Machine Assistant Technician" under Agriculture Skill Council of India (ASCI) at KVK campus during 20<sup>th</sup> November to 18<sup>th</sup> January 2025.

This particular course intends, a person that helps to manage and operate machinery required to harvest crops in the field, as well as the subsequent processing and handling of those crops after they are harvested with aiming to minimize losses and optimize quality throughout the post-harvest process.

Such type of training program will help to provide a new dimension on harvest and post-harvest operation of different agricultural commodities in the district and will promote development of new entrepreneurs in the region. I strongly believe that; this training is very important and wish a grand success and hope the compendium will provide adequate information on major commodities of Nayagarh district.

I hope many effective deliberations during the training program will be helpful for the aspirants and will provide a great opportunity for learning experience and eye-opening exposure to all the participants from various agricultural sectors.

Date: 03.02.2025 OUAT, Bhubaneswar (Prof. Prasannajit Mishra)





Collector & District Magistrate Nayagarh, Govt. of Odisha





Sri Akshay Sunil Agrawal, I.A.S Collector & District Magistrate

#### **MESSAGE**

Krishi Vigyan Kendra, OUAT, Nayagarh has undertaken an ambitious program focussing on Entrepreneurship Development through Skill training on "Harvest and Post Harvest Machine Assistant Technician" under Agriculture Skill Council of India (ASCI).

This training program will foster entrepreneurship, income generation and employment opportunities for participants and their communities. This program also encourages the participants to pursue their careers in agriculture sectors through mechanization in particular for strengthening the livelihood.

This particular course includes providing Hands-on training along with exposure visits to various processing units to establish and manage small scale agri-business, either individually or collectively and this compendium will provide a comprehensive summary on harvest and post-harvest operations of agricultural commodities in Nayagarh district.

I highly commend the Scientific team of KVK, Nayagarh for their efforts in bridging the gap between lab to land operations, ensuring effective knowledge transfer.

Date: 05.02.2025 Nayagarh, Odisha (Sri Akshay Sunil Agrawal)





## PREFACE

Agriculture Skill Council of India (ASCI) works towards capacity building by bridging gaps and upgrading skills of farmers, wage workers, self-employed & extension workers engaged in organized / unorganized segments of Agriculture & Allied Sectors. Among various job roles "Harvest and Post Harvest Machine Assistant Technician" is one of job roles in developing the skills of manpower in emerging areas of agriculture.

Proper time and method of harvesting are important to avoid yield losses in the field. Both early and late harvest is detrimental with respect to yield and quality. The importance of post-production operations is as important as pre-production operations. The utilization of certain crops in different ways as one component and storage and handling of the product as a second component. Certain crops are specially produced and consumed, which are not known or totally neglected by people. The harvested produce should be properly threshed, cleaned and graded. Appropriate method of drying and proper storage is very much necessary.

This particular compendium on Harvest and Post Harvest Machine Assistant Technician can solve problems attached to production and post production operations of agricultural commodities in Nayagarh district. The proper knowledge is very much necessary for right time harvest and minimizing losses due to poor post-harvest handling problems which can enable to achieve a better output.

The author presented the compendium entitled "Harvest and Post-Harvest Machine Assistant Technician" a scientific and systematic manner to understand the fundamentals of harvest and post-harvest technology clearly and easily.

The dedication and tireless efforts of the Scientific Team has been pivotal to the success of this course. This publication stands as a reflection of hard work and serves as a crucial resource for the aspirants to gather technical knowledge on harvest and post-harvest operations of different agricultural commodities. This compendium is anticipated to be an invaluable resource for all stakeholders involved in agriculture sectors.





## **CONTENT**

Message

Preface

1.	Introduction	-	2
2.	Rice	-	3
3.	Post Harvest Management of Rice	-	4-9
4.	Products of Rice Bran	-	9-11
5.	Dal Processing	-	11-15
6.	Sugarcane Processing	-	15-21
7.	Cashew Apple Products	-	22
8.	Millet Products	-	22 - 23
9.	Food Safety Regulations and Standards	-	23- 24
10.	Opportunities For Micro/Unorganized Enterprises	-	24
11.	Processing and Value addition of Fruits and Vegetables	-	25 - 34
12.	Millet Processing	-	35-42
13.	Epilogue	-	43
14.	Annexure	-	44-45





## INTRODUCTION OVERVIEW OF HARVEST AND POST HARVEST OPERATION

#### HARVESTING

It is the operation of cutting, picking, plucking and digging or a combination of these operations for removing the crop from under the ground or above the ground or removing the useful part or fruits from plants.

#### Harvesting action can be done by four ways:

- 1) Slicing action with a sharp tool.
- 2) Tearing action with a rough serrated edge
- 3) High velocity single element impact with sharp or dull edge.
- 4) Two elements' scissors type action.

#### Manual harvesting involves slicing and tearing action.

#### Harvesting can be done by:

- (i) Manually operated tool
- (ii) Animal drawn machine
- (iii) Mechanically operated machine.

There are a few related terms in connection with harvesting, which are as below:

**Mower:** It is a machine to cut herbage crops and leave them in swath.

**Reaper:** It is a machine to cut grain crops.

**Reaper binder:** It is a reaper, which cuts the crops and ties them into neat and uniform sheaves.

**Swath:** It is the material as left by the harvesting machine.

**Sickle:** It is a curved steel blade having a handgrip and used for harvesting by manually.

**Windrow:** It is a row of material formed by combining two or more swaths.

Wind rower: It is a machine to cut crops and deliver them in a uniform manner in a row.

Post harvest processing ensures effective utilisation of harvested produce and the quality of the end product, which ultimately tells upon the consumption and acceptance of the produce. It has been estimated that there is considerable loss in many of the agricultural products after harvest. This is either because the post harvest technology has not been developed to the desired extent or because of the special problems in the marketing of the produce.

#### **THRESHING**

Thresher is a machine to separate grains from the harvested crop and provide clean grain without much loss and damage.

During threshing, grain loss in terms of broken grain, un-threshed grain, blown grain, spilled grain etc. should be minimum.

Bureau of Indian Standards has specified that the total grain loss should not be more than 5 per cent, in which broken grain should be less than 2 per cent.

Mechanical threshers are widely accepted by the farmers.

#### A mechanical thresher consists of the following parts

- i. Feeding device (chute/tray/trough/hopper/conveyor)
- ii. Threshing cylinder (hammers/spikes/rasp-bars/wire-loops/syndicator)
- iii. Concave (woven-wire mesh/punched sheet/welded square bars) iv. Blower/aspirator v. Sieve-shaker/strawwalker.

**RICE** 





#### Harvesting of Rice

- For paddy, harvesting refers to the cutting and gathering of panicles attached to the stalks.
- Harvesting at the right time and in the right way maximizes grain yield and minimizes grain losses and quality deterioration.
- Once the plants have reached full growth (approximately three months after planting) and the grains begin to ripen-the tops begin to droop and the stem yellows-the water is drained from the fields.
- As the fields dry, the grains ripen further and harvesting is commenced.

#### Stage of Harvest

- Many factors must be considered to obtain optimum rice harvest.
- The grain must be mature, high in quality and have proper moisture content.
- Field should be sufficiently dry to support harvesting and transport.
- Timely harvesting ensures good grain quality, high market value and improved consumer acceptance.
- The right stage for harvesting is when about 80% panicles have 80% ripened spike lets and their upper portion is straw colored. The grain contains about 20% of moisture.
- Rice should be harvested when the grains on lower part of the panicle are in hard dough stage.
- Maturity may be hastened by 3-4 days by spraying 20 % NaCl a week before harvest to escape monsoon rains.

#### **Harvesting Methods**

• Depending on the size of the operation and the amount of mechanization, rice is either harvested by hand or machine. The different harvesting systems are as follows:

#### Manual harvesting

Manual harvesting makes use of traditional threshing tools such as threshing racks, simple treadle threshers and animals for trampling or by hand using sharp knives or sickles. Gives 55-60 % grain recovery.

#### Manual harvesting and machine threshing

Rice is manually threshed, then cleaned with a machine thresher.

#### Machine reaping and machine threshing

A reaper cuts and lays the crop in a line. Threshing and cleaning can then be performed manually or by machine.

#### Combine harvesting

The combine harvester combines all operations from paddy harvesting to rice extraction - cutting, handling, threshing and cleaning. Gives 50 % recovery.





#### **Threshing**

- Threshing is the process of beating paddy plants in order to separate the seeds or grains from the straw.
- To maintain the high quality of the harvested grains, it should be threshed immediately after harvesting.
- Avoid field drying and stacking for several days as it affects grain quality due to over drying. Stacked grains of high moisture content results in dis-coloration or yellowing.

#### Manual threshing

- The manual methods of threshing are treading by feet, flail method, and beating stalks against tubs, boards or racks.
- Threshing can be done by trampling using bullocks, rubbing with bare human feet (in hills) or lifting the bundles and striking them on the raised wooden platform.
- Pedal threshers are also used.
- Freshly threshed rice must be dried well in the sun.

#### **Machine threshing**

- Mechanical threshing removes rice grains from the rice plant, speeds up threshing (thus reducing losses), and reduces labor requirements.
- Power driven stationary threshers are also used.
- Freshly threshed rice must be dried well in the sun

#### POST HARVEST MANAGEMENT IN RICE

#### REASONS FOR POST HARVEST LOSS

- 1. Poor product coming into storage
- 2. Poor storage management
- 3. Poor quality paddy + poor milling techniques Present situation Approx. 25-50% of the total grain value (quantity + quality) is lost between harvest and consumption in developing countries.

#### **DRYING**

- It is the process of removal of excess moisture from the grains
- Once dried, the rice grain, now called rough rice, is ready for processing
- Proper drying results in increased storage life of the grains, prevention of deterioration in quality, reduction of biological respiration that leads to quality loss of grains, and optimum milling recovery
- Safe moisture level as Grain = 14% & as Seed = 12%

#### **METHODS OF DRYING**

- Sun drying
- Mechanical drying
- Chemical drying





#### **Sun Drying**

- It is a traditional method of drying the paddy grains. Sun drying is the most economical method of drying grains.
- Grains are spread on drying surfaces such as concrete pavement, mats, plastic sheets and even on fields to dry naturally.

#### **Mechanical Drying**

- Drying process means drying the grains by ventilating natural or heated air through the grain mass to get it evaporated the moisture from it.
- Mechanical dryers are more reliable since drying could be done anytime of the year.

#### **Chemical Drying**

- This drying method involves the spraying of common salt solution with specific gravity of 1.1 to 1.2 on the ears of the mature paddy crop
- This treatment reduces the moisture content from 29% to 14.5% after four days.

#### **Parboiling**

- It is a pre-milling hydrothermal treatment given to unhulled rice (rough rice) to improve its milling quality, nutritive value, cooking quality and storability
- The process is accomplished in three steps: soaking, steaming and drying
- Single boiling method involves soaking the unhulled rice in water at room temperature followed by open steaming for 20-30 minutes using iron kettles and then sun drying
- In double streaming method, the unhusked rice is first steamed to raise its temperature and then soaked in cold water for 24-36 hrs. After soaking, it is steamed second time for 20-30 minutes followed by sun drying.

#### Milling

- Milling is the process wherein the rice grain is transformed into a form suitable for human consumption, therefore, has to be done with utmost care to prevent breakage of the kernel and improve the recovery.
- Brown rice is milled further to create more visually appealing white rice.
- After harvesting and drying, the paddy is subjected to the primary milling operation which includes de-husking as well as the removal of bran layers (polishing) before it is consumed. In this process the rice which is obtained after milling is called raw rice.
- Another process through which rice is obtained after milling is called "Parboiling Rice." Nearly 60% of the total rice produced in India is subjected to parboiling.
- Rice milling losses may be qualitative or quantitative in nature. Quantitative or physical losses are manifested by low milling recovery while low head rice recovery or high percentage of broken kernel reflects the qualitative loss in rice grains.



## E SE ICAR

#### Milling involves several steps, including:

- Pre-cleaning: Removing foreign materials like soil, weed seeds, and straw
- Dehusking: Removing the husk, which makes up about 20% of the paddy
- Paddy separation: Separating the paddy from the brown rice
- Whitening or polishing: Whitening or polishing the rice
- Separation of white rice: Separating the white rice
- Rice mixing: Mixing the rice
- Mist polishing: Mist polishing the rice
- Rice weighing: Weighing the rice

#### Methods of Milling

- Traditional Method Before the advent of mechanical milling, hand-pounding traditional method of rice milling was in practice. In fact, hand-pounding rice has got more nutritive value as compared to machine milling rice
- In hand-pounding, a variety of implements is used such as: Mortor and Pestle Dhenki Hand Stone (Chakki)

#### **Mechanical Method**

- With the introduction of mechanized mills, hand-pounding method has steadily decreased because it could not compete with machine mills.
- The conventional mills in use can be categorized into three main types: Huller mills Sheller-Huller mills Sheller-Cone Polisher mills

#### **Modern Rice Mills**

• Milling of Paddy:Milling paddy is the process of turning unpolished rice into refined white rice for consumption.

#### **Shelling and separation:**

- Separation hulling for removal of husk from paddy, it is necessary to apply shearing action / friction to the grain surface Hulling of paddy is done to remove the husk from the paddy grain.
- Due to application of friction, there is some breakage of grain too.
- After hulling, the resultant mixture contains brown rice, husk, broken grain and some unhulled grain.
- To have brown rice, these constituents need to be separated.

#### Hulling

- Hulling of Paddy machines are known by different names such as hullers, huskers, dehuskers, shellers. Machines used in hulling paddy are under-runner disc huller, Engleberg huller, centrifugal sheller and the rubber roll sheller.
- The efficiency of a huller is defined as the percentage of grain hulled with minimum breakage.
- Efficiency of a huller depends upon the construction of machine, its precision, its maintenance, adjustment and its operation.





- Rice Huller is used to perform the shelling and/or whitening process using a specially chilled, hard cast iron cylinder rotating inside a hardened screen.
- The degree of milling is controlled by: a) the outlet slide, which regulates the residence time in the Machine b) the huller blade, which regulates the severity of the process and is adjustable to suit the variety and condition of the rice being milled, to keep breakage to a minimum.
- Under runner huller consists of two horizontal cast-iron discs, partly coated with abrasive layer. The bottom disc rotates and is vertically adjustable whereas the top disc remains fixed. The clearance between the two discs depends on the variety of paddy and the condition of the grain.
- Paddy is fed into the centre of the machine at controlled rate and dehusking is done by compression and friction while coming out of the periphery of the discs.

#### Under runner disc huller advantage capacity:

- It is higher than steel huller type.
- Percentage of cracked and broken grains produced is less than that produced by steel huller type. More power efficient than steel huller type.
- Easy to operate. Low operation cost.
- Machine is very durable.
- Hulling efficiency is nearly comparable to rubber roll huller.

#### Under runner disc huller disadvantage capacity:

- It is very heavy and requires a moderate size operating space.
- This process scratches the rice kernel. As the abrasive stone wears, sand and silicon dislodges and mixes with rice and bran.
- Machine capacity is less than the rubber roll sheller. Huller efficiency in this machine is 85% 90%.
- Does not work well with paddy of mixed varieties (different kernel dimensions)

#### Rubber roll huller

- It consists of two rubber rolls, one is fixed in position while other is adjustable to have desired clearance between the rolls.
- Both the rolls having same diameter (150- 250 mm) and same width (60-250 mm) but rotate in opposite directions at differential speeds.
- One roll moves about 25 percent faster than the other. The difference in peripheral speeds subjects the paddy grains falling between the rolls to a shearing action that strips off the husk.
- The hulling efficiency of this machine is better than other hulling machines

#### **Husk Separation**

• Rice huller is a mixture of brown rice, paddy, husk, brokens, bran and dust. The bran and dust are usually separated through an oscillating sieve with fine perforations. Brokens are separated through self- cleaning sieves. Husk separation is done using husk aspirators available in various designs.





- Paddy Separation: After separation of husk, dust, bran and small brokens, a mixture of brown rice and paddy is obtained. The paddy is separated from brown rice using paddy separator.
- There are 3 types of paddy separators namely: compartment type, tray type and screen type.
- However, the most commonly used paddy separator is compartment type.
- Compartment type separator

#### It consists of a number of compartments in one, two, three or four decks.

- The number of compartments depends upon capacity of rice mill and varies from 5 to 80.
- Up to 10 compartments single deck is used
- \* Up to 12-20 compartments, two decks are used
- Up to 51 compartments, 3 decks are used
- Up to 80 compartments 4 decks are used.

**Rice Shifter:** These sifters are used to separate broken rice from head rice. **Polishing** 

- Polishing is the process of removal of bran layer in brown rice.
- After harvesting and drying, the paddy is subjected to the primary milling operation which includes dehusking as well as the removal of bran layers (polishing) before it is consumed.
- The rice obtained after this process is called raw rice

#### **Quality and Grading**

- Quality of rice is not always easy to define as it depends on the consumer and the intended end use for the grain.
- Grain quality is not just dependent on the variety of rice, but quality also depends on the crop production environment, harvesting, processing and milling systems.

#### Characteristics Considered for Grading of Milled Rice

- Dead rice, brokens and brewers percentages
- Defectives
- Foreign matter
- Presence of paddy
- Whiteness
- Chalkiness
- Moisture content





#### **OBJECTIVES OF STANDARDS AND GRADES**

- To ensure only edible rice reaches the consumer.
- To improve post harvest practices so as to eliminate or reduce waste.
- To improve agronomic practices to increase farm yields.
- To improve processing practices for better milling recoveries and for market expansion.
- To protect consumers from price/quality manipulation.

#### **Grades of Indian Rice**

- Common variety: Short bold & long bold rice
- Fine variety: Medium slender rice
- Superfine variety: Long slender & short slender rice

#### **STORAGE**

Storage is the process of keeping grains, whether in bags or in bulk, in a storage structure designed to protect the stored product from inclement weather and pests for a short or long period of time to await processing or movement to other location.

#### Grains are stored for either of the following reasons:

- To provide uniform supply of food throughout the year, because grains are produced seasonally while consumption is fairly uniform throughout the year.
- To provide reserve for contingencies such as flood, drought and other calamities.
- · To speculate on a good price either in domestic or in the export market.
  - The grains are stored at three different levels, such as:
- · Producer's Level
- · Trader's Level
- Urban Organizational Storage Level
   The methods followed for storing the grains are:
- · Storage in bags
- Loose storage
- Storage in bags is convenient for short term storage, where grain is intended for very early onward movement.
- For short term storage, no control measures against insects are needed.
- In loose/bulk storage method, large quantity of grains can be stored in per unit volume of space and the infestation of insects/pests is lower.
- The basic requirements of a good storage practice are: a healthy, clean, and uniformly dried grain, and a structure that will maintain a suitable environment that will prevent pests

## PRODUCTS OF RICE BRAN: Bran WAX OIL RICE BRAN

It is the hard outer layer of grain and consists of aleurone, pericarp, germ and a part of endosperm. When bran is removed from grains, the grains lose a portion of their nutritional value. Bran removal amounts to 4% to 9% weight of the paddy milled. Bran is characterized by its high fat and protein content along with vitamins, minerals and many other useful chemicals.





#### USE OF RICE BRAN

• Bran Edible grade oil Industrial grade crude oil Free fatty acid manufacture Plasticizers Tocoferol Rice bran wax

#### **RICE PRODUCTS**

#### Husk:

- Rice husk contains 38% cellulose and 32% lignin and fuel materials.
- Paddy husk contains silica so it is abundantly used as fuel for boilers and households.
- It is also used for bedding materials in the livestock and poultry industry, ash cement or component for making light weight cement blocks for partition walls, in tile industry, oil absorbent, washing powder, and mulch.

#### Bran:

- Commonly used as animal feed in most developing countries, either directly or mixed with other ingredients as done by commercial feed producers.
- Rice bran has a high percentage of oil, which can be extracted by solvents.
- Edible bran oil is used extensively in India. Bran is also used in food processing industry for making biscuits and speciality cookies.
- Spoiled bran can be used in compost and used as organic fertiliser.
- De-oiled bran can be safely used as animal feed. India also produces edible bran oil and plans to increase output over the next few years.

**RICE BROKENS:** Used in breakfast cereals, baby foods and for making several food items with rice flour base, such as noodles, rice cakes and rice delicacies. Rice brokens are an export item from large commercial rice mills

#### RICE PROCESSED PRODUCTS

#### VALUE ADDITION

- 1. Processed Products
- 2. Fermented Products based on rice
- 3. Extruded Products

#### **Parched Rice**

- It is prepared by throwing rice in sand heated to a high temperature in an iron or ud pan.
- On stirring rice become crackle and swell. Then the content of the pan are removed and sieved to separate the parched rice from sand.
- Parboiled rice is used for making such rice.

#### **Expanded rice**

- It is a traditional convenience food widely consumed in India.
- The paddy is soaked in water over night, drained and either steamed or dry roasted in sand for parboiling.
- The parboiled paddy is milled, salted and roasted in sand for expansion.

#### **Puffed Rice**

• This is the popular ready to eat snack product is obtained by puffing milled rice.



- The rice is gently heated without sand to reduce moisture slightly.
- Then mixed with salt solution and again roasted to prepare puffed rice

#### Flaked Rice

Traditionally it is prepared from soaked paddy. After heat treatment and immediate flattering using a flaking machine. Flaked rice is thin and white, red in colour.

#### **Quick Cooking rice**

• It is made by steeping polished rice in water to moisture content of 35%, cooking under pressure and drying.

#### 2. RICE - FERMENTED PRODUCTS

#### Idli

Idli is a small, white acid-leavened, and steamed cake made by bacterial fermentation of a thick batter made from rice and dehulled blackgram dal.

#### Dosa

Dosa is another feremented products made out from fermented batter of rice and pulse in the propostion ranging from 6:1 to 10:1

#### 3. RICE EXTRUDED PRODUCTS

- Extrusion is a process that combines several unit operations including mixing, kneading, shearing, heating, cooling, shaping and forming.
- It involves compressing, and working raw material like Flours, starches, protein, salt, sugar and other minor ingredients to form a semi solid mass and it is allowed to pass through a restricted opening.
- Heat is applied by steam injection or indirectly through a heated barrel.
- The extrusion cooking is also called a high temperature short time(HTST) process.
- Rice based extruded products include sevai, idiappam, murukku (chakli) rice based vadagam etc.
- Rice based noodles and noodles from fermented rice flour are popular.

#### Murukku

Raw rice and black gram were ground in a mill separately and sieved through 80 BS sieve and used for the preparation of murukku instant mix.

#### **DAL PROCESSING**

Some post-harvest equipment used for dal includes:

#### Dal mill machine

Removes the husk and splits pulses to improve their taste and digestibility.

#### Polishing equipment


Removes powder from dehusked splits and applies oil and water to give the dal a shine. This can be done with a cylindrical hard rubber roll, leather belts, emery cone polisher, or rollers with brushes.

#### Hand-operated pulse dehusking machine

It can dehusk and split pulses like pigeonpea, chickpea, soybean, and peas. It can dehusk 40–60 kg of pulses per hour.







#### Cleaning and grading

- Raw pulses need to be cleaned before milling.
- Normally rotary or reciprocating screen cleaners are used.
- Rotary screen graders are common in northern part of the country, whereas in the southern part, reciprocating screen graders are used.
- These graders separate the grains into different fractions based on size.
- Light impurities are removed with the help of blower or suction fans.
- Rotary screen cleaner/grader mainly consists of four compartments fitted with screens in sequence of increasing opening size.
- Smallest grains falls at the first compartment, whereas the largest one falls in the last column.
- Slope is given towards the direction of grain flow for ease of grain movement. Low RPM around 18–30, is maintained to ensure proper grading of raw material.
- Mild steel or wooden body is used to house these compartments depending upon choice of the customer.
- Reciprocating flat screen grader usually consists of three screens to separate the grain fractions.
- Blower is provided to remove dust, dirt and other fine impurities. Stroke length of 4-5 cm is provided for the reciprocating unit.





#### **Dehusking**

- Typically, carborundum/emery coated rollers are used for dehusking of different pulses.
- Cylindrical or taper rollers are used for the purpose.
- The foundation of taper rolls is kept horizontal whereas cylindrical rolls are mounted with inclination to the horizontal.
- This system facilitates ease of grain movement inside the drum. Normally, a slope of 15 cm for entire length of machine is recommended.
- Body of the roller is made of wood or steel on which mixture of carborundum/emery, chemical cement and salts are applied in layer of uniform thickness.
- The granule size of emery varies for crop to crop and type of operation to be performed on the grain.

#### Oil/Water applications

- This machine is used for mixing of oil/water to the pitted pulses. Screw conveyors with full flight or cut screw are used.
- The screw slowly moves the grain forward, with the oil/water application at the entry of the conveyor.
- The grain gets thoroughly mixed with oil/water while travelling the mixer length. Cut screw flights, commonly used in southern India, also serve the purpose of agitator and increases retention time for better mixing.

#### **Drying**

- Generally, sun drying on rooftop or in open drying yard is practiced. Since sun drying is a weather dependent process, the operation of the mill stops during rainy and cloudy seasons.
- To make conventional milling plants operational round the year, artificial or mechanical drying is essential.
- Accordingly, various manufacturers developed some batch or continuous dryers for use in dal mills. In order to avoid sun drying, CFTRI, Mysore has developed thermal treatment process using dryers.

#### **Splitting**

- To split the dehusked pulses and pulse seeds, roller mills, under runner disk made of medium size (24–30 No.) granules.
- Under disk runner machine consists of two horizontal disks with 1.25 cm emery coating. One of the disks is fixed whereas other one rotates.
- This rubbing action causes splitting of dehusked whole (i.e., Gota). It can also be used for splitting of black gram, chickpea, lentil, green gram and soybean.
- The capacity of the machine depends upon size and speed of the disk. Attrition mills are vertical or horizontal stone or emery disks.
- Some millers to minimize breakage during splitting use elevator and hard surface combination.
- Dehusked splits are dropped from a height of about 3-5 m on a hard surface to obtain splits. Impact splitter machine consists of mild steel blades mounted on shaft inside an enclosed casing.
- Rotating blades throw the 'gota' on stationary hard casing splits. The 'gota' is split by impact in the machine





#### Dal grading and Gota separation

- Gota separation from milled fractions is a big challenge.
- Whenever the grain is passed through emery roll, some part of grain is converted into dehusked whole called 'Gota'.
- It is difficult to separate dehusked whole grain from almost similar size whole grain using normal size grading machines.
- Gota' separating machine, based on surface properties was developed by CFTRI, Mysore.
- Combination of rotary and reciprocating screens are used in modern pulse milling plants to separate 'gota'.
- This machine is used for separation of 'gota' and whole grains, splits and broken.

#### **Polishing**

- Dal polishing denotes to removal of powder from dehusked splits and application of oil and water to impart shine and luster to the finished dal.
- Cylindrical hard rubber roll, leather belts or emery cone polisher is used for the purpose.
- Rollers mounted with brushes can also be used to impart shining to the dal.
- Powder particles are removed by rubbing action.
- Battery of screw conveyors with mild abrasive surfaces, like nylon rope or velvet cloth, can also be used for repeated rubbing.
- Accordingly, they are named as nylon or velvet polisher. Depending upon level of polishing 2, 3, 4 or 5 screw conveyors can be used.
- Oil and water polisher is similar to the oil/water treating machine.
- Water or oil is applied at the entrance of the unit, worm inside the mixing unit acts as a polisher, often dal is required to be dried prior to final packaging.

#### Powder and husk separation

- Husk and powder are separated from dehusked pulses, using suction fan or blower.
- This unit may end into a cyclone separator and collected in bags, in order to reduce environmental hazard of fine dust in the plant premises.

#### Material handling

- Bucket elevators are widely used in dal mills for vertical grain movement. Usually drying of grains takes place on the roof.
- This saves time and energy lost in material handling. In large capacity plants, bucket elevators often control feeding inside the mill.

#### **Post Harvest Processing:**

Processing of pulses is of primary importance in improving their nutritive value. The processing methods used are soaking, germination decortications, cooking and fermentation.

**1 Soaking:** Soaking in water is the first step in most methods of preparing pulses for consumption. As indicated above, soaking reduces the oligosaccharides of the raffinose family. Soaking also reduces the amount of phytic acid in pulses.





- Germination: Germination improves the nutritive value of food pulses. The ascorbic acid content of pulses increases manifold after 48 hours germination. Germinated and sprouted pulses have been used to prevent and cure scurvy. The riboflavin, niacin, choline and biotin contents of all pulses increase during germination. The germination process reduces and/or eliminates most of the antinutritional and toxic factors in several pulses.
- Decortication: A simple method is to soak the seeds for a short time in water; the husk takes up more water than the seeds and may be easily separated by rubbing while still moist. In the alternative, the soaked grains may be dried and the husk removed by pounding and winnowing. Roasting also renders the husk easier to separate. Roasted legumes like those of Bengal gram and peas are widely used in India.
- 4. Cooking: Cooking destroys the enzyme inhibitors and thus improve the nutritional quality of food pulses. Cooking also improves the palatability.
- 5. Fermentation: The processing of food pulses by fermentation increases their digestibility, palatability and nutritive value. Fermentation process improves the availability of essential amino acids and, thus, the nutritional quality of protein of the blend. In general, the nutritive value of the legume based fermented foods has been shown to be higher than their raw counterparts.
- 6. Pulse milling:
  - The removal of the outer husk and splitting the grain into two equal halves is known as milling of pulses.
- A. Pulses are usually converted into Dhal by decutilating and splitting. Both dry and wet milling processes are employed. By and large carborundum emery rollers are used for dehusking and burr grinders for splitting. Decuticling is seldom complete in single pass requiring multiple passes, each pass producing 1.5 to 2% fines reducing recovery of dal.
- B. Basic processes in dhal milling are cleaning, dehusking, splitting, separation and bagging. Major variation is involved with dehusking process only. Dhals like Arahar, urad, moong and lentil are difficult to dehusk as a result repeated operations by dehusking rollers are required. Rewetting and drying is done to loosen portions of husk sticking after repeated rolling. Linseed oil is used to impart shine or better appeal to the milled dal.
- C. To facilitate dehusking and splitting of pulses alternate wetting and drying method is used. In India trading milling methods produce dehusked split pulses. Loosening of husk by conditioning is insufficient in traditional methods. To obtain complete dehusking of the grains a large number of abrasive force is applied in this case as a result high losses occur in the form of brokens and powder. Yield of split & pulses in traditional mills are only 65 to 75% due to the above losses compared to 82 to 85% potential yield.

#### Dal Processing Unit for small scale industry

Sl.	Machineries	Unit cost (Approx)(Rs)
No		
1	Mini Dal Mill	60,000/-
2	Cleaner-Grader-polisher	30,000/-
3	Thresher-cum-Pearler	15,000/-
4	Threshing and pearling of minor millets	1500/-





#### SUGARCANE PROCESSING

#### Harvesting

In India harvesting of sugarcane is carried out at 10 to 18 months stage, depending upon the planting time and crop maturity. In sub-tropics, autumn crop is harvested at 15-month stage, whereas spring and summer (late-planted) crops at 10-12 months. Early varieties are harvested at 10 months stage, mid-late 10-12 months and late after 12-month stage. In tropical zone, crop is harvested after 16-18 months stage.

Manual Harvesting

Hand knives, cutting blade or hand axes are used for manual harvesting. It requires skilled labourers as improper harvest of cane leads to loss of cane and sugar yield, poor juice quality and problems in milling due to extraneous matter.

#### Sugarcane Stripper

- It is used to de-topping of leaf.
- Capacity-50kg/hr

#### **Mechanical Harvesting**

- Sugarcane is harvested by mechanical harvester which move along the rows of cane removing the leafy tops of the cane and cutting the stalk into short pieces or "billets". Billets are loaded into bins which are towed alongside the harvester.
- When full, the bins are taken by road or tramway to the sugar mill.
- The field capacity of mechanical cane harvesters varies with the size (2.5 to 4 ha per day of 8 hours.

#### PROCESSING OF JAGGERY

#### Selection of Sugarcane

Selection of good quality matured sugarcane having high sucrose content, high purity and low colloids is an important first step towards manufacturing quality jaggery.

#### Harvesting and cleaning of cane

Cane with brix more than 21 per cent should be harvested close to the ground and cleaned off dry leaves, trashes, green tops, roots and mud clods. Remove 2-3 immature internodes along with top portion. Soil adhering to the cane should be removed. The cleaned sugarcane should be immediately transported to the crushing yard and crushed within 24 hours of harvest. Delay in crushing may cause inversion losses.

#### Extraction of juice

For crushing of cane, horizontal power crusher able to extract 60 to 70% juice was used. Horizontal roller crushers yield 2-4% more juice compared to vertical roller crusher. At this process two products are obtained raw sugar cane juice as main product and bagasse. Level of extraction and concentration of soluble solids of sugar cane juice affects directly productivity. Percentage of extraction(Weight of juice\*100/Weight of cane) depends on operation conditions of crusher, which also has a significant effect on quality and quantity of sugar cane juice. Factor affecting extraction of juice are gap between rollers (6mm, crushing – 1mm extracting), size and speed of rollers, orientation of rollers, grooves on rollers(grip, preparation and juice drainage) and bearing and bushes.

#### **Settling tank**

The juice is then collected through underground PVC pipeline into the juice settling tank covered with thick layered cloth where small particle impurities are filtered from the juice. The juice is allowed to remain in the tank for one hour so that heavy impurities settles down due to gravity and the clean juice is then pumped into the specially designed open pans kept on furnace.

#### Juice filtration

The juice that comes out of crusher has some impurities, such as ions, colloid and dirt of soil, waste pulp and wax. Colloid are made up of soil, wax, fats, proteins, vitamins, glues, pentine, taninin and coloring material. Its percentage is low which ranges from 0.05 up to 0.3%. ionic and molecular dispersion correspond basically to sugars and minerals constituents. Hence the filtration of juice is essential to obtain jaggery free of soluble solids and impurities. The extracted juice is filtered with three layered wire mesh or thick cloth to separate undissolved impurities like trashes, pieces of bagasse, and roots etc. It is then passed through vibro or mechanical filters to get clear juice.





#### Juice Clarification

Clarification process eliminates solids in suspension, colloidal substances and coloring compounds by the accumulation of these impurities. Once pre-filtration process is finished sugar cane juice continues its progress to the first furnace at a temperature close to room temperature to be heated up to 50-55°c, which allows the formation of particles of higher density and larger sizes, which are easier to be removed. At this point, part of substances that generate, impurities to the finished product are still in suspension without being removed due to their sizes, unless, a clarification agent is added. The pre-heated juice is moved to a second furnace where a clarification agent is supplied to increase coagulation of impurities. Coagulation comprises of a series of chemical and physical reaction between the coagulant and the solution of sugar cane juice and as a result of this reaction the forces that keep together the particles are destabilized. Clarification of juice loaded in pans is very important for making light yellow coloured, crystallized and impurities free jaggery, which is edible and also suitable for storage. The dissolved impurities in the juice are removed with the help of herbal/vegetative clarificants. Phyto-clarificants are rich in gums& mucilage which are poly-glucuronic acid and act as a flocculent. These polymers dissociate on heating and form charged particles with large number of active sites to attract negatively charged impurities (colloidal ,colouring& ash forming impurities). Some of these are mentioned below.


#### TABLE: 1 COMMONLY USED VEGETABLE

Sl No.	Name	Parts which are Used	Additional gm per quintal juice	Brief method of using
1.	Bhindi	Stem and roots	45-50	Dipped in water for about 2-4 hrs, pound and rubbed. Thus Mucilaginous liquid obtained is added
2.	Groundnut	Seed	70-75	Soaked, decorticated ground with water is mixed after straining

TABLE: 2
Chemical clarificants are also being used. Some of them are mentioned below.

Chemical & Quantity required per q juice	Action	Immediate effect on product	Remarks
Hydros (Sodium hydro sulphite) 3.5g	Colour bleaching	Brightens colour temporarily	Hastens colour darkening and process of spoilage within a month.
Lime (Calcium oxide) 100 to 125ml of 10% lime	Removes juice acidity. Helps in clarification	Liming to pH 6.3 to 6.6 results in good quality. Useful in solidification of jaggery from waterlogged, lodged canes. Excess liming results in hard jaggery.	Better storibility of hard jaggery





<u>a</u>






#### Proximate composition of sugar and jaggery (per 100 gm)

Constitutent	Sugar	Jaggery
Sucrose, g	99.5	60-85
Reducing sugar, g	-	5 - 15
Protein, g	-	0.4
Fat, g	-	0.1
Calcium, mg	-	8.0
Iron, mg	-	11.4
Phosphorus,mg	-	4.0
Total minreals,g	0.05	0.6 – 1.0
Moisture, g	0.2 – 0.5	5-10
Energy, kcal	398	312 - 383

Gur also has 168mg carotene, 0.02 mg thiamine, 0.05mg riboflavin, 0.05 mg vitamin d







#### Concentration

The juice is boiled till it reaches striking point temperature. (115oC – 118oC). Churning is done for uniform heating hence better product quality. It is then removed from the pan and kept in the wooden/ steel cooling pan. It is the final stage of the whole production process, it occurs at a temperature higher than boiling point of water. Inversion of sucrose depends on temperature, pH and the remaining time in the furnace. From 100°C inversion of sucrose speeds up significantly, due to this reason sugar cane juice should remain for the shortest time in the furnace and run a pH close to 5.8 to avoid an increment in reducing sugars.

#### Cooling and moulding

The juice concentrate is thoroughly mixed with the laddle. The slurry is, then poured into the moulding frames of desired shapes and sizes (2.5 cm cubical shape weighing 20-22 gm or 2.5 cm x 2.5 cm x 1.25 cm square shaped weighing 10-11 gm) developed by IISR, Lucknow.

#### MACHINERIES FOR JAGGERY PROCESSING

Power Operated Crushers Juice recovery: 60-70%

Horizontal roller crusher: 2 - 4%

better recovery

Capacity: 2-3 qtls/hr – 10 qtls/hr Power needed: 5 hp - 16 hp

#### **Equipments for Sugarcane Jaggery Preparation for small scale industry**

Sl.	Machineries	Unit cost (Approx)(Rs)
No		
1	Improved Four Roller Sugarcane Crusher	50,000/-
2	Modified Electronic Thermometer	4,000/-
3	Churner	7500/-
4	Modified Hardness Tester (Used for testing hardness of	2,000/-
	solid jaggery. It is useful in distinguishing the jaggery	
	samples for storage, transport and various other purposes)	
5	Juice Boiling Pan	1,00,000/-(250kg capacity)
6	Sugarcane Juice Collection and Settling Tank	50,000/-
7	Boiling Pan Tipping Mechanism	10,000/-
8	Jaggery Moulding Frame(cube shaped jiggery)	5,000/-
9	Rectangular Shaped Jaggery Moulding Frame	5,000/-
10	Drying-cum-Storage Bin	2,000/-
11	Furnace(Boiling and concentration of sugarcane juice)	20,000/-
12	Solar Dryer for Jaggery(Facilitates jaggery packaging and	30,000/-
	elongates its' shelf life.)	

#### **JAGGERY PACKAGING**

The packaging material to be used must be carefully chosen, taking into account both practical and marketing specifications, in order to ensure the consistency of the spices during handling, transport, storage, and delivery. In general, the packaging specifications for spices are listed below:

- To protect the product from spillage and spoilage.
- To provide protection against atmospheric factors such as light, heat, humidity, and oxygen.
- The selected packaging materials should have high water vapour and oxygen barriers.
- The packaging material should have a high barrier property to prevent aroma/flavour losses and in gross of external odour.





- The volatile oil contained in the spice substance has a tendency to react with the packaging material's inner/contact layer, often leading to a greasy and sticky packet with the printed matter being smudged.
- Therefore, the wrapping material should be resistant to grease and oil and be compliant with the commodity.
- The packaging content should, in addition to the above practical specifications, have good machinability, printability and be readily available and disposable

## **SUGARCANE JUICE READY TO SERVE (RTS) Process Of Preparation**

Sugarcane Cleaning Soaking Washing Crushing Filtering Homogenization Bottling Pasteurization Cooling Storage

- Cleaning: Remove mud and other unwanted material from the sugarcane before juicing.
- Milling: Break the sugarcane's structure and extract the juice.
- Clarification: Remove impurities from the juice through coagulation, flocculation, and precipitation. The insoluble precipitate absorbs and drags the impurities from the juice.
- Filtration: Filter the juice to get a clear solution.
- Preservation: Add preservatives, additives, and Flavors to the juice. Pasteurization at 70°C for 10 minutes can increase the shelf life of sugarcane juice to up to 90 days if refrigerated.
- Bottling: Store the juice in bottles and cork them.

#### THE PACKAGE TYPES GENERALLY USED AS CONSUMER PACKS ARE:

- Glass bottles of various sizes and shapes with labels and provided with metal or plastic caps. The plastic caps have added inbuilt features of tamper evidence, dispensing, grinding, etc.
- Printed tin plate container with/without dispensing systems
- Printed tin plate container with/without dispensing systems
- Plastic containers with plugs and caps with dispensing and tamper evidence features
- Printed flexible pouches pillow pouch, gusseted pouch, stand-up pouch.
- Lined cartons

#### **Material Of Packaging**

Some of the commonly used laminates are:

- Polyester/metallised polyester/LDPE
- BOPP/LDPE
- BOPP/metallised polyester/LDPE
- Polyester/Al foil/LDPE



#### **Bag Filling Machine**



Packaging machinery



**Automatic FFS Machine** 

#### CASHEW APPLE PRODUCTS

#### Cashew apple juice

Freshly harvested cashew apples are washed in running water and ensured to be free from soil debris or microbial spoilage. The juice extraction can be achieved through juice extractor.430mg/liter quantity of gelatin solution is added to the juice to precipitate tannin.

#### Cashew apple squash

The procedure for preparation of juice and squash is similar. But the consistency of squash can be achieved by adding more sugar and citric acid. Freshly harvested cashew apples are washed in running water and ensured to be free from soil debris or microbial spoilage. The juice extraction can be achieved through juice extractor. 430mg/liter quantity of gelatin solution is added to the juice to precipitate tannin and preservatives viz., 6 g of sodium benzoate and 100 g of citric acid will be added. The squash can be diluted with three times of water and serve.

#### **CASHEW APPLE READY-TO-SERVE(RTS)**

The required amount of water with sugar (200 g sugar / 1 L water) and citric acid (5g) are boiled with continuous stirring. Amount of 200 ml clarified cashew apple juice and 100 ml of any fruit juice are added after switching off the flame. The content is cooled and packed in bottle.

#### MILLET PRODUCTS

Finger millet also known as ragi in India is one of the important cereals occupies highest area under cultivation among the small millets. Finger millet is comparable to rice with regard to protein (6-8%) and fat (1-2%) and is superior to rice and wheat with respect to mineral and micronutrient contents. In order to develop the value-added food products based on ragi, that can able to enrich the nutritional value and also beneficial for good health is the current need for the wellbeing of the society. Krishi Vigyan Kendra, Nayagarh provide technology for preparation of Ragi Laddu, Ragi Malt, Ragi cookies and other delicious value-added products of Ragi.





S.	Name of	Ingredient
N.	Ragi product	
1.	Multi-grainflour /Composite flour	Cleanedfingermilletseed(30%)and cleanedwheatseed(70%)
2	Ragi Malt – Weaningfood	Sproutedfingermilletseed(70%)andsproutedgreengramseed (15%) and chickpea sprouted seed (15%)
3	RagiLaddoo	Flouroffingermillets, Chickpeaandwheat, Rawaofwheat, molasses/sugar, Ghee, Cardamom, Mawa, Dry nuts.
4	RagiCake	Flour of finger millets& wheat, milk powder, dry fruits, soda, vanilla essence, katri,baking soda, sugar
5	RagiCookies	Flour of finger millets & wheat, soda, salt, baking powder, clarified butter/ghee/oil
6	RagiSev	Flouroffingermillets,gram&rice,chillipowder,salt,caraway, sesamum
7	RagiBarfi	Flouroffingermillets,rawaofwheat,sugar,drynut,drycoconut, milk, clarified butter
8	RagiHalwa	Flouroffingermillets,pulseofmoongbeanandgram,cardamom, milk, dry nut, sugar, clarified butter
9	Ragi Noodle	Ragi flour -70%, Wheat flour - 30%, Salt, Water

#### FOOD SAFETY REGULATIONS AND STANDARDS

#### INTRODUCTION

The Food Safety and Standards Authority of India (FSSAI) has been established under Food Safety and Standards, 2006 which consolidates various acts & orders that have hitherto handled food-related issues in various Departments. The FSSAI is responsible for setting standards for food so that there is one body to deal with and no confusion in the minds of consumers, traders, manufacturers, and investors. The Act aims to establish a single reference point for all matters relating to food safety and standards, by moving from multilevel, multi-departmental control to a single line of command.

#### FSSAI REGISTRATION & LICENSING PROCESS

According to Section 31(1) of Food Safety and Standards (FSS) Act, 2006, Every Food Business Operator (FBO) in the country is required to be licensed under the Food Safety & Standards Authority of India (FSSAI). As per FSS (Licensing & Registration) Regulations, 2011, Licenses and Registrations are granted to FBOs in a 3-tier system

- Registration for petty FBOs with annual turnover less than Rs 12 lakhs
- State license for medium-scale food manufacturers, processor and transporters
- Central License for large-scale food manufacturers, processor and transporters FSSAI registration is done online on the FSSAI website through Food Safety Compliance System (FoSCoS)
- FoSCoS has replaced the Food Licensing and Registration System (FLRS).
- Petty food business operators are required to obtain FSSAI Registration Certificate





- "Petty Food Manufacturer" means any food manufacturer, whomanufactures or sells any article of food himself or a petty retailer, hawker, itinerant vendor or temporary stall holder (or) distributes foods including in any religious or social gathering except a caterer or
- Other food businesses including small scale or cottage or such other industries relating to food business or tiny food businesses with an annual turnover not exceeding Rs. 12lakhs and/or whose production capacity of food (other than milk and milk products and meat and meat products) does not exceed 100 kg/ltr per day Any person or entity that does not classify as a petty food business operator is required to obtain an FSSAI license for operating a food business in India.

#### FSSAI License - two types - State FSSAI License and central FSSAI License

Based on the size and nature of the business, the licensing authority would change.

 Large food manufacturer/processors/transporters and importers of food products require central FSSAI license

#### Medium-sized food manufacturers, processor and transporters requires state FSSAI license.

- License period: 1 to 5 years as requested by the FBO.
- A higher fee for obtaining FSSAI license for more years.
- If a FBO has obtained the license for one or two years, renewal may be done, no later than 30 days prior to the expiry date of the license.

## OPPORTUNITIES FOR MICRO/UNORGANIZED ENTERPRISES PM-FME Scheme:


Ministry of Food Processing Industries (MoFPI), in partnership with the States, has launched an all India centrally sponsored "PM Formalisation of Micro Food Processing Enterprises Scheme (PM FME Scheme)" for providing financial, technical and business support for up-gradation of existing micro food processing enterprises. The objectives of the scheme are:

- I. Support for capital investment for up-gradation and formalization with registration for GST, FSSAI hygiene standards and Udyog Aadhar;
- II. Capacity building through skill training, imparting technical knowledge on food safety, standards & hygiene and quality improvement;
- III. Hand holding support for preparation of DPR, availing bank loan and up-gradation;
- IV. Support to Farmer Producer Organizations (FPOs), Self Help Groups (SHGs), producers cooperatives for capital investment, common infrastructure and support branding and marketing.





# Processing and Value addition of



## **SWEET POTATO PROCESSING AND USES**







## Sweet potato starch processing machine













## **Sweet Potato Products**







#### **Sweet Potato Flour**





#### **Sweet Potato Noodles**









**Sweet Potato Chips** 





#### Value Additions in Jackfruit

∑ Jackfruit, one of the **underutilized fruit**, has got the **immense potential** for value addition.

∑A wide variety of items can be prepared from jackfruit right from immature stage to well-ripened stage.

∑Each item has its own qualities in terms of taste, preference, shelf-life, etc.

Elecause of its **heaviness** and **large** size, **transportation** and **packaging** are huge problems to the successful marketing of jackfruit.

∑ Therefore, value-added products have more relevance for the commercial utility rather than the whole fruit.

∑ Jackfruit can be preserved by applying various techniques like drying, freezing, canning, or by converting it into various products.





250


ß Vacuum frying can be done with both matured and ripe jackfruit to produce a bright yellow and crunchy product.

ß Oil retains its properties without change since low temperature and pressure are involved in the process thus the oil can be reused many times for vacuum frying through this technique.

ß Nearly 90 % of oil use could be reduced compared to convention frying, making it a healthy alternative to conventional

frying.









### Jackfruit flour

- The flour prepared by milling dried jackfruit bulbs extends the shelf life of jackfruit.
- Flour from matured bulbs has a yellowish-white colour.
- This can be used as an ingredient in many of the dishes like idly, chapati, upma, pappad, etc.
- Jackfruit flour, as it is diabetic-friendly and gluten-free, can be used along with wheat flour for making soft chapattis and as a fortifier in every dish.
- Moreover, the nutritious fiber content in this flour can have several healtJackfruit Seed Powderh benefits.



## Jackfruit Seed Powder

- Jackfruit seeds are rich in nutrients and can be a supplement for wheat flour to some extent.
- Replacement of the wheat flour with jackfruit seed flour will give gluten-free products option.
- Jackfruit seed powder is used to prepare cookies along with wheat, rice bran which gives better acceptability and healthy.
- It can be fortified with flours of ragi, maize, rice, and banana and u for the preparation of pasta.

## Ready to cook (R-T-C) mature jackfruit

- Mature jackfruit bulbs can be stored for a long time by the drying method.
- The packed RTC jackfruit extends the shelf life of jackfruit.
- It can be rehydrated and used for the preparation of dishes in offseason too.
- RTC jackfruit also gives additional income to farmers and processors.









#### Retorted Tender Jackfruit (Technology for tender jackfruit in cans/retort pouches)

- Processing of tender jackfruit as a vegetable can give a quality product that fetches **better price in the** market and thus help to improve the financial status of the jackfruit growers in the state.
- Processed jackfruit products have an excellent market on the **domestic and export front**.
- The tender jackfruit from both 'varikka' and 'koozha' varieties were minimally processed and canned.
- The tender jackfruit is cleaned and cut into pieces, blanched, and sealed in cans/retort pouches along with preservatives.
- These are subjected to **retort processing**.

The retort processed tender jackfruit is **shelf-stable for one year** without any changes in its nutritive value.

The canned tender jackfruit resembles fresh jackfruit and is made available to the consumers in ready-to-eat form throughout the year.

## This is a blooming technology in the food industry and a promising technology that is accepted by consumers.










#### Osmo-dried jackfruit

- This could be prepared by a **two-stage drying process** i.e. osmotic dehydration followed by any other secondary drying.
- Osmo-dried jackfruit is an intermediate moisture food product, and is not only delicious but also conserves attractive colour and nutritional elements.
- This processed product has a six-month shelf life.
- The ripe jackfruit bulbs are deseeded and soaked in sugar syrup for osmotic dehydration and further dried using a cabinet dryer.
- The **second stage of drying** done either by traditional drying, solar drying, cabinet drying.









E 440 - Pectin

E 332 – Potassium citrate


E 224 - Potassium metabisulfite

E202 - Potassium sorbate

E122 - **synthetic red colorant** belonging to the group of azo dyes


E127 - Erythrosine or Red Dye. It is a cherry-pink/red synthetic coal tar dye

#### Paste and sauces











### **Candied fruits**

• The prepared fruit or peel is boiled in cane sugar syrup (30°B) containing 0.1% citric or tartaric acid for 10-15 minutes and then left in syrup for about 24 hours.



- Next day, the syrup concentration is raised to 40°B by adding more sugar.
- · The whole mass is boiled for about 5 minutes and left for another 24 hours.
- The process is repeated until the syrup reaches 60°B.
- Syrup strength is progressively raised to 75°B at the rate of 5°B and boiling the mass on every alternate day.
- · After syrup treatment, the fruits or the slices are removed from syrup and drained for about half an hour and sorted out to separate any defective and unwanted pieces.
- · After this, the fruit/slices are dipped for a moment in boiling water to remove the adhering syrup followed by slow drying in the shade or in a drier at 66°C for 8 to 10 h.
  - Total sugar-not less than 70%
  - · Reducing sugar- not less than 25% of total sugar











# **Packaging Materials Processed foods**



Glass

 Chemically inert and will not affect quality, odor or taste of product. It is strong, rigid and 100% recyclable.





PP/PET (polyethylene terephthalate)

· lightweight, flexible and recyclable. It can be used for both still and carbonated products.





Metal Cans

 Aluminium, Tin and steel are mainly used. They are 100% recyclable and lightweight.






Cartons

They protect the freshness, flavors and nutritional qualities, enabling distribution at ambient temperatures or under refrigerated conditions





**Different Packaging Materials Processed Products** 



(a) Layers of Brick Pack



(b) Juice in Brick Pack



(d) Juice in







(f) Beverage in Can





# **Millet Processing**

ପୁଷ୍ଟିଶସ୍ୟର ପ୍ରକ୍ରିୟାକରଣ

ଯନ୍ତ୍ରପାତିର ରକ୍ଷଣାବେକ୍ଷଣା

Dr. U. S Pal

**ଡ. ଉମା ଶଙ୍କର ପାଳ** ଗବେଷଣା ଯବ୍ତୀ ଅମଳ ପରବର୍ତ୍ତୀ ଯାନ୍ତିକ ଓ ଚୈଷୟିକ ଜ୍ଞାନ କୌଶଳ

ଭଲମାନର ଶସ୍ୟ ପାଇବା ପାଇଁ ନିମୁଲିଖିତ କେତୋଟି ଦିଗ ପ୍ରତି ଦୃଷ୍ଟି ଦେବା ଉଚିତ୍

- ୧. ଅମଳ କେଣ୍ଡା ଗୁଡିକୁ ଜମିରେ ଶୁଖିବା ପାଇଁ ବେଶୀ ଦିନ ରଖନ୍ତୁ ନାହିଁ । ଶୁଖିଲା କେଣ୍ଡା ଗୁଡିକ ବେଶୀ ସମୟ ଭୂମି ସଂୟର୍ଶରେ ରଖିବା ଉଚିତ୍ର ନୂହେଁ ।
- ୨. ଅମଳ ପରେ ଗୋଟିଏ ପରିଷ୍କାର ଚଟାଣରେ ଯଥାଶୀଘ୍ର କେଣ୍ଡାଗୁଡିକ ଥ୍ରେସିଂ କରିବା ଉଚିତ୍ ଓ ଶସ୍ୟ ଥ୍ରେସିଂ ପରେ ଶୀଘ୍ର ଶୁଖାଇବା ଉଚିତ୍ । ସାଧାରଣତଃ ଏହାକୁ ପ୍ଲାଷ୍ଟିକ୍ କିନ୍ଦ। ପାଲ ଉପରେ ଶୁଖାଇବା ଉଚିତ୍ ।
- ୩. ଖରାରେ ଶୁଖାଇବା ସମୟରେ ସମାନ ଭାବରେ ଶୁଖିବା ପାଇଁ ପ୍ରତି ଘଣ୍ଟାରେ ଥରେ ଘାଣ୍ଟନ୍ତ୍ର । ଖରା ସମୟରେ ଶସ୍ୟ ଅଧିକ ଗରମ ହେବାର ସମ୍ଭାବନା ଥିବାରୁ ଘୋଡାଇ ଦିଅନ୍ତ୍ର । ବର୍ଷା ଦାଉରୁ ମଧ୍ୟ ଶସ୍ୟକୁ ସୁରକ୍ଷିତ ରଖିବା ଉଚିତ୍ ।
- ୪. ଭଲ ଭାବରେ ଶୁଖିଯାଇଥିବା ଶସ୍ୟକୁ ପବନରେ ଉଡାଇ ସଫା କରାଯାଇଥାଏ ।
- ୫. ସଫା ଶସ୍ୟକୁ ବାୟୁରହିତ ପ୍ଲାଷ୍ଟିକ ବ୍ୟାଗ୍ ବା ବନ୍ଦ ଡବାରେ ରଖି ଥିଷା, ଶୁଖିଲା ଏବଂ ସଫା ସ୍ଥାନରେ ସଂରକ୍ଷଣ କରନ୍ତୁ ।
- ୬. ଶସ୍ୟ ସଂରକ୍ଷଣ ଗୃହକୁ ସଫାସୁତର। ରଖିବା ଉଚିତ୍ ଏବଂ ଏହାର କାନ୍ଥ କିୟା ଚଟାଣରେ ଫାଟ ନଥିବା ଦରକାର ଏବଂ ଆବଶ୍ୟକସ୍ଥଳେ ବିଶୋଧନ କରିବା ଉଚିତ୍ ।
- ୭. ସଂରକ୍ଷଣ ଗୃହକୁ ବାୟୁ ମଣ୍ଡଳର ଆର୍ଦ୍ରିତା, ପକ୍ଷୀ ଓ ମୂକ୍ଷା ଆଦିରୁ ରକ୍ଷା କରିବା ନିମିଇ ବିହିତ ପଦକ୍ଷେପ ନେବା ।

# ପୃଷ୍ଟିଶସ୍ୟର ପ୍ରାଥମିକ ପ୍ରକ୍ରିୟାକରଣ

ପୁଷ୍ଟିଶସ୍ୟ ଗୁଡିକ ଅମଳ ପରେ ୧୦-୧୨% ଜଳୀୟ ଅଂଶ ପର୍ଯ୍ୟନ୍ତ ଭଲ ଭାବରେ ଶୁଖାଇ ଠିକ୍ ଭାବରେ ସଂରକ୍ଷିତ କରାଗଲେ ଏହା ବର୍ଷରୁ ଅଧିକଦିନ ରହିପାରେ । ତେବେ ଏଗୁଡିକ ଚୋପା ଲାଗିଥିବା ଅବସ୍ଥାରେ ସଂରକ୍ଷିତ କରିବା ଉଚିତ୍ ।

ପୁଷିଶସ୍ୟର ପ୍ରକ୍ରିୟାକରଣ ପର୍ଯ୍ୟାୟ ଗୁଡିକ ହେଲା ସଫା କରିବା, ଦାନାର ଆକାର ଅନୁଯାୟୀ ବର୍ଗୀକରଣ କରିବା, ଗୋଡି ଓ ଓଜନିଆ ପଦାର୍ଥ ବାହାର କରିବା, ଚଷୁ ବା ଚୋପା ବାହାର କରିବା ଇତ୍ୟାଦି । ଚୋପାଛଡା ପୁଷ୍ଟିଶସ୍ୟକୁ ଗୁଣ୍ଡ କରି କିୟା ଛୋଟ ଛୋଟ ଶସ୍ୟ ଖଣ୍ଡ ଆକାରରେ ପେଷାଯାଇ ରୋଷେଇ ଉପଯୋଗୀ କରାଯାଇଥାଏ ।



ପୁଷ୍ଟିଶସ୍ୟରେ ସମାନ ଆକାର ବିଶିଷ୍ଟ ଗୋଡି କିୟା ଓଜନିଆ ପଦାର୍ଥ ଥିଲେ, ତାହା ଗୋଡି ବାହାର କରିବା ଯନ୍ତରେ ଆକାର ଭିତ୍ତିରେ ପୃଥକ କରାଯାଇଥାଏ । ପୃଥକ ହୋଇଥିବା ଶସ୍ୟକୁ ଗୋଡି ବାହାର କରିବା ଯନ୍ତରେ ପକାଯାଇଥାଏ । ଏଥିରେ ଥିବା ନୂଆଁଣିଆ ଜାଲି ତଳୁ ଆସୁଥିବା ପବନର ପରିମାଣ ନିୟନ୍ତଣ କରି, ସେଥିରୁ ଗୋଡି ବାହାର କରାଯାଇଥାଏ । ନୁଆଁଣିଆ ଜାଲି ଉପରେ ଗୋଡି ଓ ଶସ୍ୟ ସାନ୍ଧ୍ରତା ଭିତ୍ତିରେ ଦୁଇ ୟର ହୋଇଥାଏ । ଗୋଡି ଜାଲି ସଂସ୍ପର୍ଶରେ ଉପରକୁ ଉଠିଯାଏ ଏବଂ ହାଲୁକା ଶସ୍ୟ ତଳକୁ ଆସିଥାଏ । ଶୋଷକ ଓ ଶ୍ରେଣୀକରଣ ଯନ୍ତ ସହ ସଂଯୁକ୍ତ ହୋଇ ଗୋଡି ବାହାର କରିବା ଯନ୍ତ ବଜାରରେ ମଧ୍ୟ ଉପଲବ୍ଧ ହେଉଛି ।

## **ୟେପା ବା ଚଷୁ ଛଡାଇବା**

ମାଞ୍ଚିଆ ବ୍ୟତୀତ ଅନ୍ୟ ପୁଞ୍ଜି ଶସ୍ୟ ବାହାରେ ଥିବା ଖାଇବା ଅନୁପଯୋଗୀ ଚଷୁ ପ୍ରଥମେ ବାହାର କରାଯାଇଥାଏ । ଏଗୁଡିକ ଛୋଟ ଦାନା ବିଶିଷ୍ଟ ହୋଇଥିବାରୁ, ଏଥିରୁ ଝେପା ଛଡାଇବା ଅପେକ୍ଷାକୃତ କଷ୍ଟକର । ହଞ୍ଜ କିୟା ମୋଟର ଝଳିତ ପଥର ଚକି କିୟା କୁଟିବା ଯତ୍ତରେ ଖେପା ବା ଚକ୍ଷୁ ପାରମ୍ପରିକ ଭାବରେ ବାହାର କରାଯାଇଥାଏ । ଝେପା ଛଡା ଯତ୍ତ (dehuller) ମୁଖ୍ୟତଃ ଏମ୍ବରୀ ରୋଲର୍, ରବର ରୋଲ ମିଲ୍ କିୟା ସେଷ୍ଟ୍ରିଫ୍ୟୁଗାଲ ପ୍ରକାରର ଉପଲନ୍ଧ ଅଟେ । ସେଷ୍ଟ୍ରିଫ୍ୟୁଗାଲ ମିଲରେ ଶସ୍ୟ କମ୍ ଭାଙ୍ଗିଥାଏ ଏବଂ କମ୍ ଶକ୍ତି ଖର୍ଚ୍ଚ ହୋଇଥାଏ । ଏଥିରେ ଅହ ପରିମାଣ ଶସ୍ୟରୁ ମଧ୍ୟ ଝେପା ଛଡାଯାଇପାରେ ଏବଂ ଏହାର ରକ୍ଷଣା ବେକ୍ଷଣା ଖର୍ଚ୍ଚ କମ୍ ହେଉଥିବାରୁ, ଆଜିକାଲି ଏହି ଯନ୍ତ୍ର ପ୍ରାୟ ବ୍ୟବହାର ହେଉଛି ।

ଶସ୍ୟରୁ ପ୍ରଥମେ ହାଲୁକା ଓ ଅପକ୍ ଶସ୍ୟକୁ ପୃଥକ କରିବାପରେ, ଏହି ଯନ୍ତ୍ରରେ ଝେପା ଛଡାଇବା ଉଚିତ୍ର । ଝେପା ଛଡା ଶସ୍ୟରୁ ଭଲମାନର ଦାନା ପାଇଁ ପୁଣି ଚକି ପୃଥକୀକରଣ ଯନ୍ତ ଏବଂ ରଙ୍ଗଭିତ୍ତିକ ପୃଥକୀକରଣ ଯନ୍ତ ବ୍ୟବହାର କରାଯାଇପାରେ । ଝେପାଛଡା ଶସ୍ୟକୁ ପ୍ଲାଷ୍ଟିକ ଜରିରେ ପ୍ୟାକିଂ ପରେ ଲେବଲିଂ କରି ବିକ୍ରିକରାଯାଏ । ଏହି ପୁଷ୍ଟିଶସ୍ୟ ଝଉଳରୁ ବିଭିନ୍ନ ଖାଦ୍ୟ ପଦାର୍ଥ ଯଥା ଚୂଡା, ଖଇ ଇତ୍ୟାଦି ପ୍ରୟୁତ କରାଯାଇପାରିବ ।

# ମାଷ୍ଟିଆର ପ୍ରକ୍ରିୟାକରଣ





### ମାଞ୍ଜିଆର ସଂରକ୍ଷଣ ଅବଧୃ

ଭଲଭାବରେ ଶୁଖିଥିବା ଗୋଟା ମାଣ୍ଡିଆ ବର୍ଷାଧିକ କାଳ ରଖାଯାଇପାରେ । କିନ୍ତୁ ମାଣ୍ଡିଆ ଗୁଣ୍ଡକୁ ନିମ୍ନଲିଖିତ ପ୍ରକ୍ରିୟାକରଣ ପଦ୍ଧତି ଅବଲୟନ କଲେ ଛଅ ମାସ ପର୍ଯ୍ୟନ୍ତ ରଖାଯାଇପାରିବ ।

- ୧ . ସଫା ଏବଂ ବିଶୋଧିତ ଶସ୍ୟକୁ ପେଷାଇବା I
- ୨. ଗୋଟାଦାନାକୁ ସଫ। କରିବା ପରେ ଘର୍ଷଣ କନିତ ରଗଡିବା ଯନ୍ତ୍ରରେ ଉପର ଷ୍ଟେପାକୁ ଭଲଭାବରେ ଘସି ସଫା କରିବା ।
- ୩. ଶସ୍ୟରୁ ସବୁ ବାହ୍ୟ ଅଦରକାରୀ ପଦାର୍ଥ ଭଲଭାବରେ ବାହାର କରିବା ।
- ୫ . ଶସ୍ୟ ଅଖା ଓ ସଂରକ୍ଷଣ କୋଠୀକୁ ବିଶୋଧିତ କରିବା
- ୬. ଗୁଣ୍ଡ ରଖାଯାଉଥିବା ଜାଗାକୁ ଭଲ ଭାବରେ ସଫା ସୁତରା ରଖିବା ।
- ୭ . ଉପଯୁକ୍ତ ବ୍ୟାଗ୍ରେ ପ୍ୟାକିଂ କରି ଥଣ୍ଡା ଓ ଶୁଖିଲା ସ୍ଥାନରେ ସଂରକ୍ଷଣ କରିବା ।

ମାଞିଆକୁ ଭାକିଲେ ସେଥିରେ ଥିବା ଅପପୃଷ୍ଟି ତତ୍ତ୍ୱ ନଷ୍ଟ ହୋଇଯାଏ, ଶ୍ୱେତସାରର ହକମଶୀଳତା ବଢେ ଏବଂ ଏହାର ସ୍ୱାଦ, ରଙ୍ଗ ଓ ବାସ୍ନା ରୁଚିକର ହୁଏ । ଏହାର ଗୁଣ୍ଡକୁ ବିଭିନ୍ନ ପ୍ରକାର ଖାଦ୍ୟରେ ଓ ଛତୁଆରେ ବ୍ୟବହାର କରାଯାଇଥାଏ । ମାାଞିଆରେ ୮ ରୁ ୧୦% ପାଣି ମିଶାଇ ୪ ରୁ ୬ ଘଣ୍ଟା ଛାଇରେ ରଖିବା ପରେ ବାଲିରେ ଭାଜି ମାଞିଆ ମୁଢି ମଧ୍ୟ ପ୍ରସ୍ତୁତ କରାଯାଇପାରିବ । ଏବେ ଗରମ ପବନ ଦ୍ୱାରା ମୁଢିଭଜା ଯନ୍ତ୍ର ମଧ୍ୟ ବାହାର କରାଯାଇଛି ।

ମାଞିଆ, ଗହମ, ଚୁଡା, ବୁଟ,ବାଦାମ, ଆଦିକୁ ଭାଜି ସେଥିରେ କ୍ଷୀରଗୁଣ୍ଡ, ଚିନି ଓ ଭଜା କାଳୁ ମିଶାଇ ଗୁଣ୍ଡକରି ସ୍ୱାଦିଷ୍ଟ ଛତୁଆ ପ୍ରସ୍ତୁତ କରାଯାଇଥାଏ । ଉକ୍ତ ଛତୁଆକୁ ଆଲୁମିନିୟମ ଯୁକ୍ତ ବହୁୟରୀୟ ପଲିଥିନ୍ ଜରିରେ ପ୍ୟାକିଂ ଏବଂ ଲେବଲିଂ କରି ବିକ୍ରି କରାଯାଇପାରିବ ।

# ମାଣ୍ଡିଆରୁ ଶିଶୁ ଖାଦ୍ୟ ପ୍ରସ୍ତୁତି

ମାଞିଆକୁ ଗଜା କରି ମାଲ୍ଟ ପ୍ରସ୍ତୁତ କରାଯାଏ । ଏହାଦ୍ୱାରା ମାଞିଆର ପୁଞ୍ଚିତତ୍ତ୍ୱ ବୃଦ୍ଧି ହେବା ସହିତ ହଜମଶୀଳତା ମଧ୍ୟ ବଢିଥାଏ । ମାଞିଆକୁ ଧୋଇ ସଫା କରିବା ପରେ ପାଣିରେ ୧ ୨ ଘଣ୍ଟା ବତୁରାଯାଏ । ଏହାପରେ ମାଞିଆକୁ ପାଣିରୁ ଛାଣି ସାଧାରଣ ତାପମାତ୍ରାରେ ୪୮ ଘଣ୍ଟା କନାରେ ବାନ୍ଧି ଗଜା ହେବାକୁ ଦିଆଯାଏ । ଗଜା ମାଞିଆକୁ ଶୁଖାଇବା ଯନ୍ତ୍ରରେ ୫ ୦° ସେ.ଗ୍ରେ. ତାପମାତ୍ରାରେ ୨ ରୁ ୩ ଘଣ୍ଟା ଶୁଖାଇବାପରେ ଗଜା ଓ ଚେର ଅଂଶକୁ ରଗଡି ବାହାର କରିଦିଆଯାଏ ।

ଉକ୍ତ ମାଞିଆକୁ ୭୩° ସେ.ଗ୍ରେ. ତାପମାତ୍ରାରେ ଭାଜି ୫% ପାଣି ମିଶାଇ ଦିଆଯାଏ । ଗୁଣ୍ଡ କରିବା ଯନ୍ତରେ ଏହାକୁ ପେଷାଇ ଚାଲୁଣୀରେ ଚଲାଇ ଖଦଡିଆ ଗୁଣ୍ଡକୁ ଅଲଗା କରିଦିଆଯାଏ । ଚିକ୍କଣ ଗୁଣ୍ଡକୁ ପଲିଥିନ୍ ପ୍ୟାକ୍ କିୟା ପେଟ୍ ପ୍ଲାଞ୍ଜିକ ଡବାରେ ପ୍ୟାକିଂ କରି ବିକ୍ରି କରାଯାଇପାରିବ । ଏହାକୁ ଗରମ କ୍ଷୀରରେ ସ୍ୱାଦ ଅନୁଯାୟୀ ଚିନି ସହ ମିଶାଇ ବ୍ୟବହାର କରାଯାଏ ।



ମାଞିଆ ଗୁଣ୍ଡ ମିଶାଇ ପୁଷିକର ପାମ୍ପଡ, ଏକ୍ୱଟ୍ରୁଡେଡ୍ ଖାଦ୍ୟ(କୁର୍କୁରେ ପରି), ନୁଡଲସ୍, ପାୟା, ବ୍ରେଡ, ବିୟୁଟ, ବରା, ବାରମଜା, ଦୋସା, ସୁପ୍, ଇଡଲି, ପକୋଡା, ଏବଂ ଲଡୁ ଆଦି ପ୍ରସ୍ତୁତ କରାଯାଇପାରିବ । ମାଞିଆ ଗୁଣ୍ଡ ମିଶାଇବା ଦ୍ୱାରା ଉକ୍ତ ଖାଦ୍ୟ ଗୁଡିକର ଖାଦ୍ୟଗୁଣ ବଡିଯାଇଥାଏ । ଏହା ବ୍ୟତୀତ ପାରମ୍ପରିକ ମାଞିଆ ଜାଉ ଏଚ୍ଡିପିଇ ପ୍ଲାଷ୍ଟିକ ଡବାରେ ରଖି ତାପ ପ୍ରୟୋଗ ପୂର୍ବକ ପ୍ରକ୍ରିୟାକରଣ କରି ବଜାରରେ ମଧ୍ୟ ବିକ୍ରି କରାଯାଇପାରିବ ।

ଲଘୁଦାନା ଶସ୍ୟକୁ ବିଭିନ୍ନ ଅନୁପାତରେ ମିଶାଇ ରାନ୍ଧିବାକୁ ପ୍ରସ୍ତୁତ ଶୁଖିଲା ଖାଦ୍ୟ ଯଥା ଦୋସା, ଇଡଲି, ବରା, ଉପମା, ଗୁଣ୍ଡ ରୂପେ ମଧ୍ୟ ପ୍ୟାକିଂ କରି ବଜାରରେ ବିକ୍ରି କରାଯାଇପାରିବ । ଖାଇବାକୁ ପ୍ରସ୍ତୁତ ଉପମା ଓ ଖେଚୁଡି ଗୁଣ୍ଡ ମଧ୍ୟବିକ୍ରି କରାଯାଇପାରିବ, ଯାହା ଗରମ ପାଣିରେ ମିଶାଇ ସାଙ୍ଗେ ସାଙ୍ଗେ ବ୍ୟବହାର କରାଯାଇଥାଏ ।

- ୧. ସଫା ଓ ବର୍ଗାକରଣ କରିବା ଯନ୍ତ(cleaner-cum-grader)
- 9. ଗୋଡିବାଛିବା ଯନ୍ତ୍ର
- ୪. ଚିକ୍ଲଣ ବା ପଲିସ୍ କରିବା ଯନ୍ତ
- 8. ଶୁଖାଇବା ଯନ୍ତ
- ୬. ଭାଜିବା ଯନ୍ତ
- ୭. ଗୁଣ କରିବା ଯନ୍ତ
- ୮. ଯନ୍ତ ଋଳିତ ଋଲୁଣୀ
- ୯. ପ୍ୟାକିଂ ଯନ୍ତ
- 🖲 େ. ଆବଶ୍ୟକୀୟ ଷ୍ଟିଲ୍ ଏବଂ ପ୍ଲାଷ୍ଟିକ ପାତ୍ର, ଓଜନ ଯନ୍ତ୍ର, ଟେବୁଲ୍ ଇତ୍ୟାଦି

### ପକ୍ରିୟାକରଣ ଯନ୍ତ୍ରପାତିର ରକ୍ଷଣାବେକ୍ଷଣା

ଯନ୍ତପାତି ଗୁଡିକର ସଠିକ୍ ପରିଷ୍ଟଳନା ଦ୍ୱାରା ଏହାର ଦକ୍ଷତ। ଏବଂ କାର୍ଯ୍ୟକାଳ ବୃଦ୍ଧି ପାଇଥାଏ । ସେଗୁଡିକର ଉପଯୁକ୍ତ ରକ୍ଷଣାବେକ୍ଷଣା ଓ ମରାମତି ମଧ୍ୟ କରିବା ଉଚିତ୍ ।

- ଯନ୍ତପାତିର ବ୍ୟବହାର ପରେ ଭଲ ଭାବରେ ସଫା କରିବା ଉଚିତ୍ । ପ୍ରଥମେ ଓଦା କପଡା ଓ ପରେ ବ୍ରସ୍ ଦ୍ୱାରା ସଫା କରନ୍ତୁ ।
- ୪. ପ୍ରତି ସପ୍ତାହ ବା ପନ୍ଦର ଦିନରେ ଯନ୍ତ୍ରପାତିର ବିଭିନ୍ନ ଅଂଶକୁ ତଦାରଖ କରିବା ଓ ଆବଶ୍ୟକୀୟ ପଦକ୍ଷେପ ନେବା । ନଟ୍ନ, ବୋଲୁ ଓ ଷ୍ଟୁ ଆଦି ଟାଇଟ୍ କରିବା ।
- ห. ଯନ୍ତପାତି ଋଲିବା ସମୟରେ ଅସ୍ୱାଭାବିକ ଶବ୍ଦହେଲେ, ତୁରନ୍ତ ଯନ୍ତଟିକୁ ବନ୍ଦ କରି ତଦାରଖ କରିବା ଉଚିତ୍ ।



- ୬. ପ୍ରତି ଯନ୍ତପାତିର ରକ୍ଷଣାବେକ୍ଷଣା ସମ୍ପର୍କୀୟ ସମୟ ସାରଣୀ ପ୍ରସ୍ତୁତ କରିବା ଏବଂ ଗୋଟିଏ ରେଳିଷ୍ଟରରେ ରକ୍ଷଣାବେକ୍ଷଣ ସମ୍ପନ୍ଧୀୟ ବିବରଣୀ ଲିପିବଦ୍ଧ କରିବା ।
- ପନ୍ଧପାତି ଗୁଡିକୁ ବାୟୁର ଆର୍ଦ୍ରତା ଏବଂ ମୂଷା ଦାଉରୁ ରକ୍ଷା କରିବା । ଯନ୍ତ୍ରର ସମୟ
   ଆଗମନ ଓ ନିର୍ଗମନ ଦ୍ୱାରାକୁ ଯନ୍ତ୍ର ଋଲି ନଥିବା ସମୟରେ ବନ୍ଦ ରଖିବା ।
- ୧୦. ଯନ୍ତ୍ରପାତି ଗୁଡିକ କଂକ୍ରିଟ୍ ଚଟାଣ ଆଧାରରେ ନଟ୍, ବୋଲ୍ଟ ଦ୍ୱାରା ଭଲ ଭାବରେ ବସାଇବା ।

## 

- ୧. ଯନ୍ତପାତିର ବେରିଂ ଅକାମୀ ହେବା
- (କ) ବିଭିନ୍ନ ଯନ୍ତପାତିରେ ଲାଗିଥିବା ବେରିଂରେ ନିୟମିତ ଗ୍ରୀଜ୍ ଦେବା ।
- (ଖ) ମଝିରେ ମଝିରେ ତଦାରଖ କରି ବେରିଂ ଭାଙ୍ଗିବା ପୂର୍ବରୁ ନୂଆ ଲଗାଇବା
- 9. ଯାନ୍ତ୍ରିକ ଋବିଗତ ତ୍ରୁଟି
- (ଖ) ଯନ୍ତ୍ରକୁ ଓଭରଲୋଡିଂରେ ନ ଚଲାଇବା ।
- ୩. ଅଧିକ ବିଦ୍ୟୁତ୍ ଶକ୍ତି ନେବା ବା ଓଭରଲୋଡିଂ
- (କ) ନିୟନ୍ତିତ ହାରରେ ଯନ୍ତକୁ ଶସ୍ୟ ଛାଡିବା ।
- (ଖ) ଓଭରଲୋଡିଂ ଜନିତ ସତର୍କ ସୂଚନାଘଣ୍ଟି କିୟା ରିଲେ ଲଗାଇବା ।
- ୪. ସଫା ଓ ଶ୍ରେଣୀକରଣ ଯନ୍ତ
- (କ) ନିର୍ଗମନ ଦ୍ୱାରକୁ ଆବଶ୍ୟକ ମୁତାବକ ଖୋଲିବା I
- (ଗ) କାମ ଶେଷ ହେବାପରେ ଜାଲି ସଫାକରିବା ।
- ୫. ଗୋଡି ବାଛିବା ଯନ୍ତ
- (କ) ଆବଶ୍ୟକ ମୁତାବକ ପବନ ପଶିବା ଦ୍ୱାରକୁ ଖୋଲିବା ଯେପରି ଗୋଡି ପଛକୁ ଯିବ ଓ ଦାନା ଆଗକୁ ଗଡି ଆସିବ ।
- ୬. ଷୋପା ଛଡାଇବା ଯନ୍ତ୍ର
- (କ) ଯନ୍ତର ଆଗମନ ଓ ନିର୍ଗମନ ଦ୍ୱାରକୁ ଆବଶ୍ୟକ ମୁତାବକ ନିୟନ୍ତଣ କରି ଯନ୍ତ ଭିତରକୁ ଶସ୍ୟଦାନା ଛାଡିବା ଯେପରି ଅଧିକ ଗୁଣ୍ଡ ନ ହୋଇ ଷୋପା ଠିକରେ ଛାଡିବ ।
- ୭. ଗୁଷ କରିବା ଯନ୍ତ
- (କ) ଗୁଣ୍ଡର ଆବଶ୍ୟକତା ଅନୁଯାୟୀ ଜାଲି ବଦଳାଇବା I
- (ଖ) ସଠିକ୍ ମାତ୍ରାରେ ଦାନା ଯନ୍ତ ଭିତରକୁ ଛାଡିବା I





### ଲଘୁଶସ୍ୟର ମାନ

ଖାଦ୍ୟ ନିୟମକ ମାନ ଅନୁସାରେ ଗୋଟା କିୟା ଷେପାଛଡା ଲଘୁଶସ୍ୟରେ କଳୀୟ ଅଂଶର ପରିମାଣ ସର୍ବାଧିକ ୧୩%, ଅନ୍ୟାନ୍ୟ ଖାଇବା ଶସ୍ୟର ସର୍ବାଧିକ ୨%, ବାହ୍ୟ ପଦାର୍ଥର ପରିମାଣ ସର୍ବାଧିକ ୧%, ଭଙ୍ଗା ଓ ପୋକା ଶସ୍ୟ ସର୍ବାଧିକ ୪% ଏବଂ ଅପକ୍ ଓ ସଂକୃଚିତ ଶସ୍ୟର ପରିମାଣ ସର୍ବାଧିକ ୫% ମଧ୍ୟରେ ରହିବା ଦରକାର । ଏତଦ୍ ଭିନ୍ନ ମାଞ୍ଜିଆ ଗୁଞ୍ଜରେ କଳୀୟ ଅଂଶର ପରିମାଣ ସର୍ବାଧିକ ୧୦% ଏବଂ ମାଲ୍ସରେ ସର୍ବାଧିକ ୫% ମଧ୍ୟରେ ରହିବା ଆବଶ୍ୟକ । ଏଥିରେ ଇଭରିକ୍ ଏସିଡ୍ର ମାତ୍ରା କିଲୋଗ୍ରାମ ପିଛା ୧୦୦ ମି.ଗ୍ରା.ରୁ ଅଧିକ ହେବା ଉଚିତ୍ ନୁହେଁ । ଏଥିରେ କୌଣସି ପ୍ରକାର ବିଷାକ୍ତ ପଦାର୍ଥ ଓ ଶସ୍ୟ, ରାସାୟନିକ ରଙ୍ଗ ଏବଂ ମୂଷାର କେଶ ଓ ମଳ ମିଶି ନଥିବା ଆବଶ୍ୟକ । ଏହାର ପ୍ୟାକେଟରେ ସବୁ ତଥ୍ୟର ସୂଚନା ଥିବା ଦରକାର ।

### ଲଘୁଶସ୍ୟର ପ୍ରସ୍ତୁତ ଗୁଣ୍ଡର ମାନ

ସଫା ଶସ୍ୟକ୍ କଳରେ ଗୁଣ୍ଡକରି ଏବଂ ଉପଯୁକ୍ତ ଛିଦ୍ରଯୁକ୍ତ କାଲିରେ ଚଲାଇ ଲଘୁଶସ୍ୟର ଗୁଣ୍ଡ ପ୍ରସ୍ତୁତ କରାଯାଏ । ଏଥିରେ କୌଣସି ଅସ୍ୱଭାବିକ ଗନ୍ଧ, ଜିଅନ୍ତାପୋକ କିୟା ମୃତ ପୋକର ଅଂଶ ନଥିବା ଉଚିତ୍ ।

ବିଭିନ୍ନ ମାନ	ମାଶ୍ଚିଆ	ଜ୍ୱାର	ଲଘୁଶସ୍ୟର ମିଶ୍ର ଅଟା
ଜଳୀୟଅଂଶ, ସର୍ବାଧିକ %	60	6 9	9 9
ଅଶୋଧିତ ତନ୍ତୁ ଜାତୀୟ ପଦାର୍ଥ, ସର୍ବାଧିକ %	8.8	-	- 9
ଅଶୋଧିତ ପୁଷ୍ଟିସାର, ସର୍ବନିମ୍ନ %	9.0	Г.8	Г.0
ଅମ୍ନରେ ଅଦ୍ରବୀଭୁତ ଭସ୍ମ, ସର୍ବାଧିକ %	0.68	0.08	0.68
ଗୁଣ୍ଡର ଆକାର	୧ମି.ମି.	୧ ମି.ମି.	୧ ମି.ମି.
ଇଉରିକ ଏସିଡ୍, ମି.ଗ୍ରା./କି.ଗ୍ରା. ସର୍ବାଧିକ %	600	600	600

### ଲଘୁଶସ୍ୟ ପ୍ରକ୍ରିୟାକରଣ ଶିଳ୍ପପାଇଁ ପରିଷ୍କାର ପରିଚ୍ଛନ୍ନତା ନିୟମାବଳୀ

ଦୂଷିତ ଖାଦ୍ୟ ଏବଂ ଚ୍ଚଳର ବ୍ୟବହାର ଦ୍ୱାରା ରୋଗ ବ୍ୟାପିଥାଏ । ତେଣୁ ଖାଦ୍ୟ ପ୍ରକ୍ରିୟାକରଣର ପ୍ରତି ପର୍ଯ୍ୟାୟରେ ସଫାସୁତର ରହିଲେ ରୋଗରୁ ରକ୍ଷା ପାଇବା ସହିତ ଖାଦ୍ୟର ସଂରକ୍ଷଣ ଅବଧି ବଢିଥାଏ ।

- ପ୍ରକ୍ରିୟାକରଣ ଶିଳ୍ପ ପରିଷ୍କାର ସ୍ଥାନରେ ଏବଂ ସଫା ପରିବେଶରେ ପ୍ରତିଷା କରିବା ଦରକାର ।
- ପ୍ରକ୍ରିୟାକରଣ ଶିଳ୍ପରେ କଞ୍ଚାମାଲ୍ ଓ ଉତ୍ପାଦ ସଂରକ୍ଷଣ ତଥା ପ୍ରକ୍ରିୟାକରଣ ନିମିଉ ପର୍ଯ୍ୟାପ୍ତ ସ୍ଥାନ ଥିବା ଆବଶ୍ୟକ ।
- ୩. ପ୍ରକ୍ରିୟାକରଣ ଗୃହ ସଫା, ଆଲୋକିତ, ବାୟୁ ଚଳାଚଳ ଉପଯୋଗୀ ହୋଇଥିବା ସଙ୍ଗେ ସଙ୍ଗେ ଯିବା ଆସିବା ପାଇଁ ମୁକ୍ତ ଜାଗା ଥିବା ଉଚିତ୍ ।
- ୪. ଚଟାଣ, ଛାଡ ଓ କାନ୍ଥ ଭଲ ଅବସ୍ଥାରେ ଚିକ୍କଣ ରଖିବା ଦରକାର ଯେପରିକି ସଫା କରିବା ସହଜ ହେବ ।
- ପ୍ରକ୍ରିୟାକରଣ ଏବଂ ସଂରକ୍ଷଣ ଗୃହକୁ କୀଟପତଙ୍ଗ ରହିତ କରିବା ସହିତ ଦରକାର ମୁତାବକ କୀଟନାଶକ ବ୍ୟବହାର କରାଯାଇପାରେ । ଝରକା, କବାଟ, ଏବଂ ଅନ୍ୟାନ୍ୟ ଖୋଲା ଜାଗାକୁ ଜାଲିଦ୍ୱାରା ବନ୍ଦ କରାଯିବା ଉଚିତ୍ ।





- ୬. ପ୍ରକ୍ରିୟାକରଣରେ ବ୍ୟବହୃତ କଳ ପିଇବା ଉପେଯାଗୀ ହେବା ଆବଶ୍ୟକ ଏବଂ କଳଯୋଗାଣ ସବୁବେଳେ ଉପଲନ୍ଧ ହେବା ଦରକାର । ଆବଶ୍ୟକ ସ୍ଥଳେ ପାଣିଟାଙ୍କିର ବ୍ୟବସ୍ଥା ମଧ୍ୟ କରାଯାଇପାରେ ।
- ଯେଉଁ ପାତ୍ର କିୟା ଯନ୍ତପାତି ବ୍ୟବହାର ଦ୍ୱାରା ଖାଦ୍ୟ କ୍ଷତିକାରକ ଧାତବ ପଦାର୍ଥ ଦ୍ୱାରା ଦୃକ୍ଷିତ ହେବାର ସମ୍ଭାବନା ଥାଏ, ତାହା ବ୍ୟବହାର କରିବା ଉଚିତ୍ ନୃହେଁ ।
- ୯. ସବୁ ଯନ୍ତପାତି ଗୁଡିକ ଭଲ ଭାବରେ ସଫା କରି, ଧୋଇ, ଶୁଖାଇ ଠିକ୍ ସ୍ଥାନରେ ରଖାଯାଏ ଯେପରି ଜୀବାଣୁ କିୟା ଫିମ୍ପି,ହେବ ନାହିଁ ।
- ୧୦. ଯନ୍ତପାତି ଗୁଡିକ କାନ୍ଥଠାରୁ ଦୂରକୁ ବସାଯାଇଥାଏ ଯେପରିକି ସେଗୁଡିକ ଠିକ୍ରେ ଅନ୍ଧାନ କରିହେବ ।
- ୧୧. ଜଳ ଓ ବର୍ଜ୍ୟବୟୁ ନିଷ୍କାସନ ନିମିତ୍ତ ସଠିକ୍ ବ୍ୟବସ୍ଥା ଥିବା ଦରକାର I
- ୧୨. ଶ୍ରମିକମାନେ ସଫା ସୁତରା ରହିବା ସଙ୍ଗେ ସଙ୍ଗେ ପ୍ରକ୍ରିୟାକରଣ ସମୟରେ ନିର୍ଦ୍ଧାରିତ ପୋଷାକ, ସଫା ଆଫ୍ରନ୍, ଗ୍ଲୋଭ୍ସ ଓ ଟୋପି ପିନ୍ଧିବା ଉଚିତ୍ ।
  - ୬. ପ୍ରକ୍ରିୟାକରଣରେ ବ୍ୟବହୃତ କଳ ପିଇବା ଉପେଯାଗୀ ହେବା ଆବଶ୍ୟକ ଏବଂ କଳଯୋଗାଣ ସବୁବେଳେ ଉପଲନ୍ଧ ହେବା ଦରକାର । ଆବଶ୍ୟକ ସ୍ଥଳେ ପାଣିଟାଙ୍କିର ବ୍ୟବସ୍ଥା ମଧ୍ୟ କରାଯାଇପାରେ ।

  - ଯେଉଁ ପାତ୍ର କିୟା ଯନ୍ତପାତି ବ୍ୟବହାର ଦ୍ୱାରା ଖାଦ୍ୟ କ୍ଷତିକାରକ ଧାତବ ପଦାର୍ଥ ଦ୍ୱାରା ଦୂକ୍ଷିତ ହେବାର ସମ୍ଭାବନା ଥାଏ, ତାହା ବ୍ୟବହାର କରିବା ଉଚିତ୍ ନୂହେଁ ।
  - ୯. ସବୁ ଯନ୍ତପାତି ଗୁଡିକ ଭଲ ଭାବରେ ସଫା କରି, ଧୋଇ, ଶୁଖାଇ ଠିକ୍ ସ୍ଥାନରେ ରଖାଯାଏ ଯେପରି ଜୀବାଣୁ କିନ୍ଦା ଫିମ୍ପି,ହେବ ନାହିଁ ।
  - ୧୦. ଯନ୍ତ୍ରପାତି ଗୁଡିକ କାନ୍କଠାରୁ ଦୂରକୁ ବସାଯାଇଥାଏ ଯେପରିକି ସେଗୁଡିକ ଠିକ୍ରେ ଅନୁଧାନ କରିହେବ ।
  - ୧୧. ଜଳ ଓ ବର୍ଜ୍ୟବୟୁ ନିଷ୍କାସନ ନିମିତ୍ତ ସଠିକ୍ ବ୍ୟବସ୍ଥା ଥିବା ଦରକାର I
  - ୧୨. ଶ୍ରମିକମାନେ ସଫା ସୁତରା ରହିବା ସଙ୍ଗେ ସଙ୍ଗେ ପ୍ରକ୍ରିୟାକରଣ ସମୟରେ ନିର୍ଦ୍ଧାରିତ ପୋଷାକ, ସଫା ଆଫୁନ, ଗ୍ଲୋଭସ ଓ ଟୋପି ପିନ୍ଧିବା ଉଚିତ୍ ।
- ୧୩. ସଂକ୍ରାମକ ରୋଗରେ ଆକ୍ରାନ୍ତ ଶ୍ରମିକକୁ ଖାଦ୍ୟ ପ୍ରକ୍ରିୟାକରଣ କାର୍ଯ୍ୟପାଇଁ ଅନୁମତି ଦିଆଯିବ ନାହିଁ ।କୌଣସିବ୍ୟକ୍ତିର କଟା କିୟା ଖଣ୍ଡିଆ ହୋଇଥିଲେ ତାକୁ ଘୋଡାଇ ରଖିବା ଉଚିତ୍ ଏବଂ ସେ ଖାଦ୍ୟର ପ୍ରତ୍ୟକ୍ଷ ସଂୟର୍ଶରେ ଆସିପାରିବ ନାହିଁ ।
- ୧୪. ଶ୍ରମିକ ନଖ ଠିକ୍ରେ କାଟିବା ଉଚିତ୍ । କାମ ପୂର୍ବରୁ କିୟା ପ୍ରତିଥର ପାଇଖାନା ବ୍ୟବହାର ପରେ ହାତକୁ ସାବୁନ୍ରେ ଭଲ ଭାବରେ ଧୋଇବା ଦରକାର । ଖାଦ୍ୟ ପ୍ରକ୍ରିୟାକରଣ ବେଳେ ଦେହ କିୟା ମୁଣ୍ଡ କୁଣ୍ଡାଇବା ଉଚିତ୍ ନିହେଁ ।
- ୧୫. ଶ୍ରମିକ ମାନେ ଢିଲା ଅଳଙ୍କାର ଆଦି ପିନ୍ଧିବା ଉଚିତ୍ ନୁହେଁ ।
- ୧୬. ଖାଦ୍ୟ ପ୍ରକ୍ରିୟାକରଣ ସମୟରେ ଖାଇବା, ପାନ ୟେବାଇବା, ସିଗାରେଟ୍ ଟାଣିବା କିୟା ନାକ ପୋଛିବା ମନା ।
- ୧୭. ଅପମିଶ୍ରଣ ନହେବା ପାଇଁ ରଖାଯାଇଥିବା ପ୍ରତିଟି ପଦାର୍ଥ ଏବଂ ବିକ୍ରିପାଇଁ ଉର୍ଦ୍ଦିଷ୍ଟ ଦ୍ରବ୍ୟକୁ ଉପଯୁକ୍ତ ସୂଚନା ସହ ଘୋଡାଇ ରଖିବା ଉଚିତ୍ ।
- ୧୮. ପରିବହନ ପାଇଁ ଉତ୍କୃଷ୍ଣମାନ ସଫା ଏବଂ ଭଲ ଅବସ୍ଥାରେ ଥିବା ଦରକାର ।





- **୧୯.** ଖାଦ୍ୟ ପରିବହନ ସମୟରେ ସଠିକ୍ ତାପମାତ୍ରା ବଜାୟ ରଖିବା ଉଚିତ୍ର ।
- କୀଟନାଶକ ତଥା ଅନ୍ୟାନ୍ୟ ରାସାୟନିକ ପଦାର୍ଥ ଖାଦ୍ୟ ସଂରକ୍ଷଣ କିୟ। ପ୍ରକ୍ରିୟାକରଣ ସ୍ଥାନରୁ ଦୂରରେ ରଖିବା ଉଚିତ୍ ।
- ୨୧. ପ୍ରକ୍ରିୟାକରଣ ଘରେ ପଡିଥିବା ଖାଦ୍ୟ ପଦାର୍ଥ ବା ଶସ୍ୟ ଦାନାକୁ ତୁରନ୍ତ ସଫା କରିବା ଦରକାର । ପାଇଖନା ଗୁଡିକୁ ନିୟମିତ ବ୍ୟବଧାନରେ ସଫା କରିବା ଉଚିତ୍ ।
- 99. ଶ୍ରମିକ ମାନଙ୍କୁ ନିରାପତ୍ତା ସମ୍ପର୍କିତ ତାଲିମ୍ ଦିଆଯିବା ଉଚିତ୍ l ଶିଳ୍ପରୁ ବାହାରୁଥିବା ବର୍ଜବସ୍ତୁ ନିର୍ଦ୍ଧାରିତ ସ୍ଥାନରେ ରଖିବା ଦରକାର l

ଏହିଭଳି ବିଭିନ୍ନ ମୁଲ୍ୟଯୁକ୍ତ ଖାଦ୍ୟ ପଦାର୍ଥ ପ୍ରସ୍ତୁତ କରି ବିକ୍ରି କରିବାକୁ ହେଲେ ନିମ୍ବୋକ୍ତ କେତୋଟି ଦିଗ ପ୍ରତି ଧ୍ୟାନ ଦେବା ଆବଶ୍ୟକ ।

- ଗୁଣାମ୍କ ଉତ୍ପାଦ ପ୍ରୟୁତ ପାଇଁ ଉପାଦାନ ଗୁଡିକର ପରିମାଣ ଓ ମାନ ନିର୍ଦ୍ଧାରଣ ଏବଂ ଉପଯୁକ୍ତ ପ୍ରକ୍ରିୟାକରଣ ପଦ୍ଧତି ଅବଲୟନ ।
- ଖାଦ୍ୟ ପ୍ରକ୍ରିୟାକରଣରେ ଉପଯୁକ୍ତ ରାସାୟନିକ ସଂରକ୍ଷକ ପଦାର୍ଥର ଯଥୋଚିତ ବ୍ୟବହାର, ଖାଦ୍ୟ ନିରାପତ୍ତା ଓ ସ୍ୱଚ୍ଛତା ନିୟମ ପାଳନ ।
- ୩. ଉପସକ୍ତ ପ୍ରକ୍ରିୟାକରଣ ସନ୍ତ୍ରପାତିର ଚୟନ, ସଠିକ ପରିଷ୍ଟଳନା ଓ ରକ୍ଷଣା ବେକ୍ଷଣା ।
- ପ୍ରକ୍ରିୟାକୃତ ଖାଦ୍ୟ ପଦାର୍ଥର ନିଜସ୍ୱ ବ୍ରାଣ୍ଡିଂ, ବଜାର ତିଆରି ଏବଂ ଜନ ସଚେତନତା ସୃଷ୍ଟି କରିବା ।

ଲଘୁଶସ୍ୟ ଉତ୍ପାଦନ ହେଉଥିବା ଅଞ୍ଚଳରେ ପ୍ରକ୍ରିୟାକରଣ ଶିଳ୍ପ ପ୍ରତିଷ୍ଠା ଦ୍ୱାରା ଏହାର ସୁବିନିଯାଗ ସହିତ ଗ୍ରାମାଞ୍ଚଳରେ ଅର୍ଥନୈତିକ ବିକାଶ ହୋଇପାରିବ । ଏହି ଉଦ୍ୟୋଗ ସ୍ୱୟଂ ସହାୟକ ଗୋଷୀ ତଥା ବେକାର ଯୁବକ ମାନଙ୍କୁ ନିଯୁକ୍ତି ସୁଯୋଗ ଦେଇପାରିବ ଏବଂ ସେମାନେ ଲାଭବାନ୍ ହୋଇପାରିବେ ।





### **EPILOGUE**

The whole content of this compendium is based on the Skill Development Training program on "Harvest and Post Harvest Machine Assistant technician" under Agricultural Skill Council of India (ASCI) conducted by Krishi Vigyan Kendra, Nayagarh, OUAT. The compendium will provide the information related to Harvest and Post Harvest operation of the major commodities of Nayagarh District Viz: Rice, Pulses, Millets, Sugarcane, Fruits and vegetables etc. Some of the technologies which are profitable and are being practised by the farmers are also included in the compendium. Along with, the presentations delivered by some of the eminent professors are added to this bulletin to provide additional information on new and advanced technologies for harvest and post- harvest handling. This record will also provide technical information which are likely to be generated within next couple of years/months with achieving sustainable livelihood option.









# NNEXURE

### \* DAL PROCESSING \*


- 1- Infrastructure:
  - · Building construction for installisation of madinaries.
  - · 2000 89 ft Building with well ventilated condition.
  - · Electribication, store room

### 2- Machinaries Required:

- Weight one chine
- Grader machine
- Destoner
- Roaster mechine
- Hauller machine
- Doyer machine
- polisher
- packaging machine

## 3. Machinary operation Process:

- · collection of good quality pulses for procusing.
- · Abter collection, Keeping pulses in good condition Weighing the pulser and record maintaining.



Grangean processing: - Firstly put the Deightad grangean in Grander machine. Grander machine removes all dust pareficles including small stone, and strong (Mc). it also grades the Grean gram in different Sizes.

### STEP-11

After grading put the items on Destoner machine it removes all micro particles and remaining impunities present in Georgian. This is Final Groungeam Fernished product ready to

### STEP-111

In this step, clean Greengram are put in treather machine. For 45 min - 60 min, after reporting Key the them 24 hs the purpar daying.

# According to & our demand, we can grind or STEP-IV to shell addition of the use the shell, we for this purpose. To remove the shell, we We 5 ml oil par 1'44 grengram. This is the Final processing step. After this step we find the final product.

### Present By

- O Manorama Dalabehera
- 3 Puspalata Preadhan
- @ Anjali . Sahoo
- 3 Rasmita Pradhan

# Breading & packaging · According to many at domand, we can make 1 kg or 500 gm packet.

## Estimated cost

- · Building X infrasture cost 3.5 Laxy
- · Electrolication 40,000
- · Madinery 4.5 Lakh
- · Total cost Rs. 8, 40, 000 /-

· Magneting with retail counter and mall, marsts.

### Project Report by

- DANIL GUMAR SAHOO
- DEBASHS PRADHAN

  DEBASHS BAIRIGANJAN
- 9 BENUCHAR DAS . ERAUMYA RANJAN SAHID

# Millet Processing Unit PROJECT Report

## Ragi Powder Machinary

Price (Approx.)

- (3) Cleaner cum Grader Machine = 35000 (8) Destroner Machine / Huller Machine = 42,000
- Sun Daying / Dayor Machine / Roaster = 59000

  Delloroizer Machine = 30,000 = 30,000
- 3 Package Machine

### = 25,000 182,000

## Malt Powder Making

- Cleaning with Water

  Sprout making sout for a day (Regi, Wheel, Green Green)

  Sprout making south for a day (Regi, Wheel, Green Green)

  Dry & Roalt in Dryer Machine at soic Tong, for s.
  Poonts. Annal reader, Sugar, Kaji, Almord, Etalish Added. House
  Pounder, Annal Reader, Sugar, Kaji, Almord, Etalish Added. House
  Pounder the small & Big Harry in purveysion.
- 1 Packing & Stacking after checking quality & Hamidity.

### MILLET PROCESSINGUES PROJECT REPORT

- O LAND 1 Decimal 2 Lating Road Facility, Boundary Association of the Road Facility, Boundary Association (Control of the Road Facility)
- As few Machine Load capacity. = 4000
- 3 Water Supply
- Storage container
- 1 Machinatics

   Cleaner cum Geader Machine = 25,000

   12,000
  - 10 Destonore Machine = 50,000
  - Dryer Machine
     Roaston Machine.
  - = 60000
- Rouse Modifies
   Pulvanizario
   Pulvanizario
   Roughy
   Sapury
   Sapury
- @ Godown For Storage (Rev Makerial & Finishad Goods)

  - Machunany Fraze
     Row Material Storage Room
     Robbed Product / Packed Items Storage Room
     Robbed Product / Packed Items
  - @ Dunping Yand For Walk Management
- 1 Operator & Manfower FOR PROCESSing
- (3) Marketing Vehicle For Trunspormatation.
  - Refer Submitted By

    RAJESH KUMAR SAHOO
  - 2 Rankanidh Behena
  - 3. Jidendan My Same
  - 4- Anupama Rana 5- Rasmita prusty

- MILLET PROJEST
- 1) House 18 20 F'
- 2 Machine p





### Dal Mill Project - 5 laxh PROJECT

- 1 House
- @ Raw Material
- @ weight Machine
- O arreading Machine
- @ 1 HP Motor &
- 1 phase Electry
- 1 De Stoner Machine 1 HP M
- & Roster Machine
- 9 Holler Machine 3 HP Motor
- 1 Dryen Machine
- 1 polishing Machine
- 1 Stock ROOM

O House - Green Asage 大大 confer only that the capello. D Row Moderial - 愛味 tolling only weight Machine that the man adjain the affer only confer only the angle the confer only the confer S silvenda clistip , Ball Machine See select silver I He Mater and agric aboil ale and angle and Bester Lloryine of I and instance of and in a feet of the instance of and in the instance of the insta hour कुरा। कार अर्थि। अर्टी 1 qay वर्र अ अरी। र्द्धा eigh do, i kosen warpene dan abu coun ab, 39-10 ताम कार्क्ट्रेट , ट्यांट्क अपन् विराजान कर्छ कार्क्ट्रेट स्टाम अपन् Harrier Harring & चुन्नुक्ट्रेट्टिंग अपन् कार्क्ट्रेटिंग स्टाम अपन् स्थार कार्य कार्य कार्य कार्य कार्य में वेश व्यक्त वार्विद्ध । स्यापेश ट क्री की पहुँ अप्र सार्वात सरीपार अर्थित 40 30-350 6-31 20/61 JET THEY Packing mg Worket of JE JOE 1








Day Processing Unit
(1) Business activity
* Raw Materials !- Greengram
* Final Product :- Mug Dal
(2) Quartity: - 100 aintal, Rs= 7,00000 ]
(3) Duration: 2 Month
(4) Row Materials analyty, Grade & size
* (grade (1) - 70 Quintal.
(4) Detail on Processing Machine Cost
* Name of the Machine cost
weight Machine 6000
Greader Machine 70000
Dreyer Machine 50000
Demonera Machine 30000
Roader Machine -
The Figure 11
Polishert 11 50,000
Packaging Machine -
(5) Treansportation cost -1 trop= 100= (341,000)
10 trip= 100a= (5000)
(6) Man Power Cost. * labour cost 1 trip = 600 (600)

(7) Operator Salary 2 Month = 1×8000 2×8000 = (6000)  ** Electricity = (6000)  ** Packaging Material (9000)  ** Mockaging Material (9000)  ** Mockaging Material (9000)  ** Grade (1) 75 Quintal  Approx nate = 70 Quintal  Approx nate = 20 Q × 100 = (2,00000)  ** Oprade (2) 20 Quintal  Approx nate = 20 Q × 100 = (2,00000)  ** Quintal × 20 = 2000  ** Quintal × 20 = 6000)  ** 1 Quintal × 20 = 6000  ** 2 Sisin × 2000 = (2,00000)	
* Electricity = (6000)  * Packaging Meterial = (9000)  Information Purify & House = (250000)  (9) Read Materials Quartity, Grade, & Size & Coop  * Grade (1) 75 Quintal  Approx rate = 20 Q X100 = (2,00000 f)  * Optode (2) 20 Quintal  Approx rate = 20 Q X100 = (2,00000 f)  * 2 Quintal Chuni :- 1 Quintal X20 = (6000)  * 1 Quintal Wast &  Project coot & Profit  12.78000 -> 11000000  (01) Dharmenton Beherra  (02) Sisin Kunar Predhan	(7) Opercatore Salary: 2 Month = 1×8000
* Electricity = (6000)  * Packeging Metrold = (9000)  Information & Building & House = (250000)  (9) Raw Materials Quantity, Grade, & Size & Cood  * Greate (1) 75 Quintal  Aprilox rate = 20 a x100 = (2,00000 f)  * Optode (2) 20 Quintal  Aprilox rate = 20 a x100 = (2,00000 f)  * 2 Quintal Churi: 1 Quintal x20 = (6000)  * 1 Quintal Wast &  Project cost & Profit  12.78000 -> 11000000  (01) Dharmenton Beheria  (02) Sisin Kunar Predhan	(8) Other Misc. Cost
* Packeging Material (4000)  3 months Building & House = (250000)  (9) Rew Materials Quantity, Grade, & SiZe & Cood  * Greate (1) 75 Quintal  Aprile rate = 20 Quintal × 20 = 2000  * 1 Quintal Wassel  1 Quintal X 20 = (6000)	* Electricity = (6000)
1	* Packaging Material = (4000)
(9) Raw Materials Quartity Grade, \$3:22 & Coop  * Grade (1) 75 Quintal  Approx note: 15 1 Quintal  Approx note: 20 Q X100 = (2,00000 1)  * 3 Quintal Chuni: 1 Quintal X20 = (6,000)  * 1 Quintal Wast 2  [10) Profit & Project cost & Profit  12.78000 -> 11000000  (01) Dharmenton Beherra  (02) Sisin Kunar Proadhan	Infortungue & Building & House = (25000)
* Grade (1) 75 Quintal  Approx rate: (2) 20 Quintal  * Oprode (2) 20 Quintal  Approx rate: 20 & ×100 = (2,00000)  * 3 Quintal Churi: 1 Quintal ×20 = (6000)  * 1 Quintal Wastle  (10) Parallel & Project Cost & Project	(9) Raw Materials Quantity, Grade, & Size & con
* Optrode (2) 20 awintal  * Optrode (2) 20 awintal  Approx rade = 20 a × 100 = 2,00000 /  * 3 awintal churi :- 1 awintal × 20 = 2000  3 awintal × 20 = (6000)  * 1 awintal wast 2  10) Profit & Project cost & Profit  12.78000 -> 1106,000  (01) Dhavementus Beherra  (02) Sisin Kunar Prodhay	* Grade (1) 75 Quintal
* Oprode (2) 20 autotal  Approx rade = 20 a × 100 = (2,00000 1)  * 3 autotal churi: 1 autotal × 20 = 2000  3 autotal × 20 = (6000)  * 1 autotal waste  (10) Product cost & Inotit  12.78000 -> 1106,000  (01) Dharmentra Beherra  (02) Sisin Kunar Prodhay	Apprex mate = 1 auintal = 000 ax120= 900
*3 Quintal Chuni: - 1 Quintal x 20 = 2000  *3 Quintal x 20 = (6000)  *1 Quintal Wast 2  [10) Profit & Profit   12.78000 -> 11,000,000  (01) Dhavementus Beherra (02) Sisin Kunar Preadhan	The state of the s
3 Quital x 20 = (6000)  * 1 Quital waste  (10) Profit & Project cost & Profit  12.78000 -> 1100000  (01) Dharmendra Beherra (02) Sisin Kunar Preadhan	Approx rade = 20 & ×100 = (2,00000 1)
(10) Profit & Profit Project Cost & Profit  12.78000 > 11,06,000  (01) Dharmentra Beherra (02) Sisin Kunar Prodhan	* 3 Quintal Chuni: 1 Quintal X 20 = 2000 3 Quintal X 20 = 6000
(01) Dharmendra Beherra (02) Sisin Kunar Preadhay	* 1 awtal waste
(02) Sisin Kumar Preadhan	
(83) Sartilata Du	(02) Sisin Kumar Preadhan
	(03) Santilata Dae

















































Publication No - 2025020425)